



LWM053 IDROFIX- polivalente trasp.-30- opaco

Safety Data Sheet dated 3/12/2018, version 1

1. IDENTIFICATION Product identifier Mixture identification: Trade name: IDROFIX- polivalente trasp.-30- opaco Other means of identification: Trade code: LW M053 Recommended use of the chemical and restrictions on use Recommended use: Industrial and professional uses (SU3 - SU22) Varnish for wood Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party Company: NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1 Importer: Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd. 7900 Henri-Bourassa Blvd. W Montreal, Quebec, Canada, H4S 1V4 Tel:+1-860-529-7704 Distrubutor: Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd. 7900 Henri-Bourassa Blvd. W Montreal, Quebec, Canada, H4S 1V4 Tel:+1-860-529-7704 Competent person responsible for the safety data sheet: msds@sivam.it Emergency phone number NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00) Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

Warning, Skin Sens. 1, May cause an allergic skin reaction. Aquatic Acute 3, Harmful to aquatic life.

Label elements Hazard pictograms:



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

Precautionary statements:

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P321 Specific treatment (see ... On this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions: None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None

Additional classification information

NFPA rating:

LWM053/1

Page n. 1 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco



3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A. Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number		Classification
>= 3% - < 5%	2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	Index number: CAS: EC: REACH No.:	603-014-00-0 111-76-2 203-905-0 01-2119475108- 36	 A.3/2A Eye Irrit. 2A H319 A.2/2 Skin Irrit. 2 H315 A.1/4/Oral Acute Tox. 4 H302 A.1/4/Dermal Acute Tox. 4 H312 A.1/4/Inhal Acute Tox. 4 H332
>= 1% - < 3%	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	Index number: CAS: EC: REACH No.:	603-096-00-8 112-34-5 203-961-6 01-2119475104- 44	1 A.3/2A Eye Irrit. 2A H319
>= 0.3% - < 0.5%	Adipohydrazide	CAS: EC: REACH No.:	1071-93-8 213-999-5 01-2119962900- 36	 A.3/1 Eye Dam. 1 H318 US-HAE/C2 Aquatic Chronic 2 H411 A.4.2/1 Skin Sens. 1 H317
11 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: CAS: EC:	613-088-00-6 2634-33-5 220-120-9	 A.2/2 Skin Irrit. 2 H315 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 A.1/4/Oral Acute Tox. 4 H302
2 ppm	reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2- methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: CAS:	613-167-00-5 55965-84-9	 A.2/1B Skin Corr. 1B H314 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Inhal Acute Tox. 3 H331

4. FIRST-AID MEASURES

LWM053/1 Page n. 2 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco

Description of necessary measures In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

- In case of eyes contact:
 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of Ingestion: Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.
- In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water. Carbon dioxide (CO2). Unsuitable extinguishing media: None in particular. Specific hazards arising from the chemical Do not inhale explosion and combustion gases. Burning produces heavy smoke. Hazardous combustion products: None Explosive properties: N.D. in volume Oxidizing properties: N.D. Special protective equipment and precautions for fire-fighters Use suitable breathing apparatus . Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures Wear personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Provide adequate ventilation. Remove persons to safety. Use appropriate respiratory protection. See protective measures under point 7 and 8. Methods and materials for containment and cleaning up Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling Avoid contact with skin and eyes, inhalation of vapours and mists. Do not use on extensive surface areas in premises where there are occupants. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Contamined clothing should be changed before entering eating areas. Do not eat or drink while working. See also section 8 for recommended protective equipment. Conditions for safe storage, including any incompatibilities Keep away from food, drink and feed. Incompatible materials: None in particular. Instructions as regards storage premises: Adequately ventilated premises. Storage temperature: Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

LWM053/1 Page n. 3 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco Control parameters 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 EU - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Notes: Skin ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 EU - TWA(8h): 67.5 mg/m3, 10 ppm - STEL: 101.2 mg/m3, 15 ppm ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9 TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3 **DNEL Exposure Limit Values** 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 Worker Industry: 125 mg/kg - Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal -Frequency: Long Term, systemic effects Worker Industry: 98 mg/m3 - Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 Worker Industry: 101.2 mg/m3 - Worker Professional: 101.2 mg/m3 - Consumer: 60.7 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 67.5 mg/m3 - Worker Professional: 67.5 mg/m3 - Consumer: 40.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 83 mg/kg - Worker Professional: 83 mg/kg - Consumer: 50 mg/kg - Exposure: Human Dermal -Frequency: Long Term, systemic effects Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects Adipohydrazide - CAS: 1071-93-8 Worker Industry: 8.6 mg/m3 - Worker Professional: 8.6 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term (repeated) PNEC Exposure Limit Values 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 Target: Fresh Water - Value: 8.8 mg/l Target: Marine water - Value: 0.88 mg/l Target: Intermittent emission - Value: 9.1 mg/l Target: Freshwater sediments - Value: 34.6 mg/kg Target: Marine water sediments - Value: 3.46 mg/kg Target: Microorganisms in sewage treatments - Value: 463 mg/l Target: Food chain - Value: 20 mg/kg Target: Soil (agricultural) - Value: 2.33 mg/kg 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 Target: Fresh Water - Value: 1.1 mg/l Target: Marine water - Value: 0.11 mg/l Target: Freshwater sediments - Value: 4.4 mg/kg Target: Marine water sediments - Value: 0.44 mg/kg Target: Microorganisms in sewage treatments - Value: 200 mg/l Target: Soil (agricultural) - Value: 0.32 mg/kg Target: Food chain - Value: 56 mg/kg Adipohydrazide - CAS: 1071-93-8 Target: Fresh Water - Value: 0.062 mg/l Target: Marine water - Value: 0.0062 mg/l Target: Freshwater sediments - Value: 0.0078 mg/kg Target: Marine water sediments - Value: 0.78 mg/kg Target: Microorganisms in sewage treatments - Value: 1000 mg/l Appropriate engineering controls: None Individual protection measures Eve protection: Eye glasses with side protection. (EN166) Protection for skin: Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands: Suitable gloves type:(EN374) Respiratory protection: Not needed for normal use. Thermal Hazards: None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:

opalescent fluid

LWM053/1

Page n. 4 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco

Odour: Odour threshold: pH: Melting point / freezing point:	typical N.D. 8.5 N.D. °C
Initial boiling point and boiling range:	> 100 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive lin	nits: N.D.
Vapour density:	> 1
Flash point:	N.A.
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	1.010 - 1.030
Solubility in water:	miscible
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects Toxicological information of the product: IDROFIX- polivalente trasp.-30- opaco a) acute toxicity Not classified No data available for the product b) skin corrosion/irritation Not classified No data available for the product c) serious eye damage/irritation Not classified No data available for the product d) respiratory or skin sensitisation The product is classified: Skin Sens. 1 H317 e) germ cell mutagenicity Not classified No data available for the product f) carcinogenicity Not classified No data available for the product g) reproductive toxicity Not classified No data available for the product h) STOT-single exposure Not classified No data available for the product i) STOT-repeated exposure

LWM053/1



LWM053 IDROFIX- polivalente trasp.-30- opaco Not classified No data available for the product j) aspiration hazard Not classified No data available for the product Toxicological information of the main substances found in the product: 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 1746 mg/kg - Source: OCSE 401 Test: LC50 - Route: Inhalation - Species: Rat = 450 Ppm - Duration: 4h Test: LC50 - Route: Skin - Species: Rabbit > 435 mg/kg 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 2410 mg/kg - Source: OCSE 401 Test: LD50 - Route: Skin - Species: Rabbit = 2764 mg/kg - Source: OCSE 402 Adipohydrazide - CAS: 1071-93-8 a) acute toxicity Test: LC50 - Route: Oral - Species: Rat = 2000 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 5.3 mg/l 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 1193 mg/kg Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 The product is harmful if inaled, swallowed or absorbed through skin. Repeated or extended exposures cause headache,drowsiness,weakness, stuttering,blurred vision,urinary albumin,kidneys demages,liver enlargement and haemolysis. Substance(s) listed on the NTP report on Carcinogens: None Substance(s) listed on the IARC Monographs: 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3. Substance(s) listed as OSHA Carcinogen(s): None Substance(s) listed as NIOSH Carcinogen(s):

12. ECOLOGICAL INFORMATION

None

```
Ecotoxicity
         Adopt good working practices, so that the product is not released into the environment.
IDROFIX- polivalente trasp.-30- opaco
        The product is classified: Aquatic Acute 3 - H402
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
         a) Aquatic acute toxicity:
                 Endpoint: EC50 - Species: Algae = 911 mg/l - Duration h: 72 - Notes: OECD 201
                 Endpoint: EC50 - Species: Daphnia = 1550 mg/l - Duration h: 48 - Notes: OECD 202
Endpoint: LC50 - Species: Fish = 1474 mg/l - Duration h: 96 - Notes: OECD 203
         b) Aquatic chronic toxicity:
                 Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 d
Adipohydrazide - CAS: 1071-93-8
         a) Aquatic acute toxicity:
                 Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96
                 Endpoint: EC50 - Species: Algae = 9.19 mg/l - Duration h: 72
                 Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
        b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Algae = 1.97 mg/l - Duration h: 72
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
         a) Aquatic acute toxicity:
                 Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
                 Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
                 Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
         b) Aquatic chronic toxicity:
                 Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
                 Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
```

LWM053/1

Page n. 6 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211 Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210 Persistence and degradability 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 90.4 - Notes: OECD 301B 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 90 - Notes: OECD TG 301 C **Bioaccumulative potential** N.A. Mobility in soil 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5 Mobility in soil: Mobile - Test: N.A. N.A. - Duration h: N.A. - Notes: N.A. Other adverse effects None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number Not classified as dangerous in the me UN proper shipping name N.A.	eaning of transport regulations.
Transport hazard class(es)	
N.A.	
Packing group	
N.A.	
Environmental hazards	
ADR-Enviromental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MA	RPOL 73/78 and the IBC Code)
N.A.	,
Special precautions	
N A	
1 4.7 1.	

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

List of substances included in the TSCA inventory: 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve, 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether, Adipohydrazide, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. List of substances not included in the TSCA inventory: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). TSCA listed substances: 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 8b, Section 8d HSDR 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in TSCA Section 8b Adipohydrazide is listed in TSCA Section 8b

- 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b.
- SARA Superfund Amendments and Reauthorization Act
 - Section 302 Extremely Hazardous Substances: no substances listed.
 - Section 304 Hazardous substances: no substances listed.
 - Section 313 Toxic chemical list: no substances listed.
- CERCLA Comprehensive Environmental Response, Compensation, and Liability Act No substances listed.
- CAA Clean Air Act

LWM053/1

Page n. 7 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco

CAA listed substances:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in CAA Section 111 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON.

CWA - Clean Water Act CWA listed substances: None

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

New Jersey Right to know Substance(s) listed under New Jersey Right to know:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Pennsylvania Right to know

- Substance(s) listed under Pennsylvania Right to know:
- 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Volatile Organic compounds - VOCs = 4.68 % Volatile Organic compounds - VOCs = 48.20 g/l Volatile CMR substances = 0.00 % Organic Carbon - C = 0.03

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H319 Causes serious eye irritation.
 - H315 Causes skin irritation.
 - H302 Harmful if swallowed.
 - H312 Harmful in contact with skin.
 - H332 Harmful if inhaled.
 - H318 Causes serious eye damage.
 - H411 Toxic to aquatic life with long lasting effects.
 - H317 May cause an allergic skin reaction.
 - H400 Very toxic to aquatic life.
 - H314 Causes severe skin burns and eye damage.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H301 Toxic if swallowed.
 - H311 Toxic in contact with skin.
 - H331 Toxic if inhaled.

Safety Data Sheet dated 3/12/2018, version 1 Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: CAS: CLP:	European Agreement concerning the International Carriage of Dangerous Goods by Road. Chemical Abstracts Service (division of the American Chemical Society). Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health

Ν LWM053/1

Page n. 8 of 9



LWM053 IDROFIX- polivalente trasp.-30- opaco

NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average