

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

Safety Data Sheet dated 7/3/2019, version 1

1. Identification

GHS Product identifier
Mixture identification:
Trade name: IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior
Other means of identification
Trade code: LWM053

Recommended use and restrictions on use
Recommended use:
Industrial and professional uses (SU3 - SU22)
Varnish for wood

Supplier's details
Company:
NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1
Importer:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666
Distributor:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:
msds@sivam.it

Emergency phone number
NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product
The product is not classified as dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements
The product is not classified as dangerous according to WHMIS 2015.

Hazard pictograms:
None

Hazard statements:
None

Precautionary statements:
None

Special provisions
None

Other hazards
None

Ingredient(s) with unknown acute toxicity
None.

3. Composition/Information on ingredients

Substances
N.A.

Mixtures
Hazardous components within the meaning of WHMIS 2015 and related classification:

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

Qty	Name	Ident. Number	Classification
>= 0.1% - < 1%	ammonia ...%	Index number: 007-001-01-2 CAS: 1336-21-6 EC: 215-647-6 REACH No.: 01-2119982985-14	<ul style="list-style-type: none"> ⚠ A.2/1B Skin Corr. 1B H314 ⚠ A.8/3 STOT SE 3 H335 ⚠ CAN-HAE/A1 Aquatic Acute 1 H400
5 ppm	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: 613-167-00-5 CAS: 55965-84-9	<ul style="list-style-type: none"> ⚠ A.2/1B Skin Corr. 1B H314 ⚠ A.4.2/1 Skin Sens. 1 H317 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ CAN-HAE/A1 Aquatic Acute 1 H400 ⚠ CAN-HAE/C1 Aquatic Chronic 1 H410 ⚠ A.1/3/Oral Acute Tox. 3 H301 ⚠ A.1/3/Dermal Acute Tox. 3 H311 ⚠ A.1/3/Inhal Acute Tox. 3 H331
2 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH No.: 01-2120761540-60	<ul style="list-style-type: none"> ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.4.2/1 Skin Sens. 1 H317 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ CAN-HAE/A1 Aquatic Acute 1 H400 ⚠ A.1/4/Oral Acute Tox. 4 H302
349 ppb	2-metil-2H-isotiazol-3-one	CAS: 2682-20-4 EC: 220-239-6 REACH No.: 01-2120764690-50	<ul style="list-style-type: none"> ⚠ A.1/2/Inhal Acute Tox. 2 H330 ⚠ A.1/3/Dermal Acute Tox. 3 H311 ⚠ A.1/3/Oral Acute Tox. 3 H301 ⚠ A.2/1B Skin Corr. 1B H314 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ CAN-HAE/A1 Aquatic Acute 1 H400 ⚠ CAN-HAE/C1 Aquatic Chronic 1 H410

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

Special protective equipment and precautions for fire-fighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.
Methods and material for containment and cleaning up
Wash with plenty of water.

7. Handling and storage

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not use on extensive surface areas in premises where there are occupants.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
Storage temperature:
Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters
ammonia ...% - CAS: 1336-21-6
ACGIH - TWA: 18 mg/m³, 25 ppm - STEL: 27 mg/m³, 35 ppm
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
TLV TWA - 0,05 mg/m³
TLV STEL - 0,23 mg/m³
DNEL Exposure Limit Values
ammonia ...% - CAS: 1336-21-6
Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 47.6 mg/m³ - Worker Professional: 47.6 mg/m³ - Consumer: 23.8 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 47.6 mg/m³ - Worker Professional: 47.6 mg/m³ - Consumer: 23.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 36 mg/m³ - Worker Professional: 36 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 14 mg/m³ - Worker Professional: 14 mg/m³ - Consumer: 2.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
PNEC Exposure Limit Values
ammonia ...% - CAS: 1336-21-6
Target: Fresh Water - Value: 0.0011 mg/l
Target: Marine water - Value: 0.0011 mg/l
Target: Intermittent emission - Value: 0.0068 mg/l
Appropriate engineering controls
None
Individual protection measures, such as personal protective equipment (PPE)
Eye protection:
Eye glasses with side protection. (EN166)
Protection for skin:
No special precaution must be adopted for normal use.
Protection for hands:

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

Suitable gloves type:(EN374)
Respiratory protection:
Not needed for normal use.
Thermal Hazards:
None

9. Physical and chemical properties

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	8.5
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 100 °C
Flash point:	N.A.
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.D.
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	1.010 - 1.030
Solubility in water:	miscible
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity
Stable under normal conditions

Chemical stability
Stable under normal conditions

Possibility of hazardous reactions
It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.
It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid
Stable under normal conditions.

Incompatible materials
None in particular.

Hazardous decomposition products
None.

11. Toxicological information

Information on toxicological effects
Toxicological information of the product:
IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

- acute toxicity
Not classified
No data available for the product
- skin corrosion/irritation
Not classified
No data available for the product
- serious eye damage/irritation
Not classified
No data available for the product
- respiratory or skin sensitisation
Not classified
No data available for the product
- germ cell mutagenicity
Not classified
No data available for the product
- carcinogenicity
Not classified

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

- No data available for the product
- g) reproductive toxicity
 - Not classified
 - No data available for the product
- h) STOT-single exposure
 - Not classified
 - No data available for the product
- i) STOT-repeated exposure
 - Not classified
 - No data available for the product
- j) aspiration hazard
 - Not classified
 - No data available for the product

Toxicological information of the main substances found in the product:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h

Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg

2-metil-2H-isotiazol-3-one - CAS: 2682-20-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

Not classified for environmental hazards

No data available for the product

ammonia ...% - CAS: 1336-21-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96

Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201

Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211

Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d

Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

2-metil-2H-isotiazol-3-one - CAS: 2682-20-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48

Persistence and degradability

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

None.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

ammonia ...% is listed in TSCA Section 8b

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b

2-metil-2H-isotiazol-3-one is listed in TSCA Section 12b, Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: ammonia ...%.

Section 313 – Toxic chemical list: ammonia ...%.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: ammonia ...% - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 693481.276 pounds.

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

CAA - Clean Air Act
CAA listed substances:
None.

CWA - Clean Water Act
CWA listed substances:
ammonia ...% is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65
Substance(s) listed under California Proposition 65:
None.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
ammonia ...%.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
ammonia ...%.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
ammonia ...%.

Volatile Organic compounds - VOCs = 3.84 %
Volatile Organic compounds - VOCs = 39.54 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.02

16. Other information

Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H410 Very toxic to aquatic life with long lasting effects.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H315 Causes skin irritation.
H302 Harmful if swallowed.
H330 Fatal if inhaled.

Safety Data Sheet dated 7/3/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
NFPA: National Fire Protection Association
NIOSH: National Institute for Occupational Safety and Health

Safety Data Sheet

LWM053 IDROFIX 30 Polivalente acqua interno - Clear WB self-seal interior

NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average