LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Safety Data Sheet dated 7/3/2019, version 1

1. Identification	
GHS Product identifier	
Mixture identification:	
Trade name:	IDROFIX 20 Polivalente acqua interno - Clear WB self-seal
	interior
Other means of identification	
Trade code:	LWM054
Recommended use and restrictions o	n use
Recommended use:	
Industrial and professional use	es (SU3 - SU22)
Varnish for wood	
Supplier's details	
Company:	
	lonviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1
Importer:	
Quincaillerie Richelieu Ltée/Ric	helieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.	
Montreal, Quebec, Canada, H4	S 1V4
Tel :+1-800-361-6000	
	Canada: Canutec (613) 996-6666
Distributor:	
Quincaillerie Richelieu Ltée/Ric	helieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.	0.004
Montreal, Quebec, Canada, H4	S 1V4
Tel :+1-800-361-6000	
	Canada: Canutec (613) 996-6666
Competent person responsible for the	e safety data sheet:
msds@sivam.it	
Emergency phone number	20.02.00204.1 (Manday Friday 8.00, 15.00)
	-39 02 90304.1 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Ni	guarda - Milan - Tel. +39 02 66101029 (24 h)
2. Hazard identification	
Classification of the hazardous produce	
The product is not classified as	dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements The product is not classified as dangerous according to WHMIS 2015. Hazard pictograms: None Hazard statements: None Precautionary statements: None Special provisions None Other hazards None Ingredient(s) with unknown acute toxicity None.

LWM054/1 Page n. 1 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

3. Composition/Information on ingredients

Substances

N.A. Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	ldent. Numb	er	Classification
>= 0.1% - < 1%	ammonia%	Index number: CAS: EC: REACH No.:	1336-21-6 215-647-6	 A.2/1B Skin Corr. 1B H314 A.8/3 STOT SE 3 H335 CAN-HAE/A1 Aquatic Acute 1 H400
5 ppm	mixture of: 5-chloro-2- methyl-4-isothiazolin-3- one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: CAS:	613-167-00-5 55965-84-9	 A.2/1B Skin Corr. 1B H314 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Inhal Acute Tox. 3 H331
2 ppm	1,2-benzisothiazol- 3(2H)-one; 1,2- benzisothiazolin-3-one	Index number: CAS: EC: REACH No.:	2634-33-5 220-120-9	 A.2/2 Skin Irrit. 2 H315 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 A.1/4/Oral Acute Tox. 4 H302
349 ppb	2-metil-2H-isotiazol-3- one	CAS: EC: REACH No.:	2682-20-4 220-239-6 01- 2120764690 -50	 A.1/2/Inhal Acute Tox. 2 H330 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

LWM054/1 Page n. 2 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary Treatment: None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media Suitable extinguishing media: Water. Carbon dioxide (CO2). Unsuitable extinguishing media: None in particular. Specific hazards arising from the hazardous product Do not inhale explosion and combustion gases. Burning produces heavy smoke. Hazardous combustion products: None Explosive properties: N.D. in volume Oxidizing properties: N.D. Special protective equipment and precautions for fire-fighters Use suitable breathing apparatus . Collect contaminated fire extinguishing water separately. This must not be discharged into drains Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety. See protective measures under point 7 and 8. Methods and material for containment and cleaning up Wash with plenty of water.

7. Handling and storage

Precautions for safe handling Avoid contact with skin and eyes, inhalation of vapours and mists. Do not use on extensive surface areas in premises where there are occupants. Do not eat or drink while working. See also section 8 for recommended protective equipment. Conditions for safe storage, including any incompatibilities Keep away from food, drink and feed. Incompatible materials: None in particular. Instructions as regards storage premises: Adequately ventilated premises. Storage temperature: Store at ambient temperature.

 8. Exposure controls/personal protection Control parameters
 LWM054/1
 Page n. 3 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

ammonia ...% - CAS: 1336-21-6 ACGIH - TWA: 18 mg/m3, 25 ppm - STEL: 27 mg/m3, 35 ppm mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 TLV TWA - 0.05 mg/m3 TLV STEL - 0,23 mg/m3 **DNEL Exposure Limit Values** ammonia ...% - CAS: 1336-21-6 Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 36 mg/m3 - Worker Professional: 36 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 14 mg/m3 - Worker Professional: 14 mg/m3 - Consumer: 2.8 mg/m3 -Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects **PNEC Exposure Limit Values** ammonia ...% - CAS: 1336-21-6 Target: Fresh Water - Value: 0.0011 mg/l Target: Marine water - Value: 0.0011 mg/l Target: Intermittent emission - Value: 0.0068 mg/l Appropriate engineering controls None Individual protection measures, such as personal protective equipment (PPE) Eve protection: Eye glasses with side protection. (EN166) Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Suitable gloves type:(EN374) Respiratory protection: Not needed for normal use. Thermal Hazards: None

9. Physical and chemical properties

Appearance and colour:	opalescent fluid	
Odour:	typical	
Odour threshold:	N.D.	
pH:	8.5	
Melting point / freezing point:	N.D. °C	
Initial boiling point and boiling ra	ange: > 100 °C	
Flash point:	N.A.	
Evaporation rate:	N.D.	
Solid/gas flammability:	N.A.	
Upper/lower flammability or exp	losive limits:	N.D.
Vapour pressure:	N.D. (20 °C)	
Vapour density:	>1	
Relative density:	1.010 - 1.030	

LWM054/1

Page n. 4 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Solubility in water:	miscible	
Solubility in oil:	partial	
Partition coefficient (n-octanol/w	vater):	N.D.
Auto-ignition temperature:	N.D. °C	
Decomposition temperature:	N.D. °C	
Viscosity:	N.D.	

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation Not classified

No data available for the product c) serious eye damage/irritation

Not classified

No data available for the product

- d) respiratory or skin sensitisation Not classified
 - No data available for the product
- e) germ cell mutagenicity
 - Not classified
 - No data available for the product

f) carcinogenicity Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

- h) STOT-single exposure Not classified
 - No data available for the product
- i) STOT-repeated exposure
 - Not classified

No data available for the product

i) aspiration hazard

LWM054/1 Page n. 5 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Not classified No data available for the product Toxicological information of the main substances found in the product: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg 2-metil-2H-isotiazol-3-one - CAS: 2682-20-4 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg Substance(s) listed on the NTP report on Carcinogens: None. Substance(s) listed on the IARC Monographs: None. Substance(s) listed as OSHA Carcinogen(s): None. Substance(s) listed as NIOSH Carcinogen(s): None. **12. Ecological information** Ecotoxicity Adopt good working practices, so that the product is not released into the environment. IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior Not classified for environmental hazards No data available for the product ammonia ...% - CAS: 1336-21-6 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96 Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211 Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d LWM054/1 Page n. 6 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d 2-metil-2H-isotiazol-3-one - CAS: 2682-20-4 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48 Persistence and degradability 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B Bioaccumulative potential N.A. Mobility in soil N.A. Other adverse effects None

13. Disposal considerations

Safe handling and methods for disposal Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number Not classified as dangerous in the meaning of transport regulations. UN proper shipping name N.A. Transport hazard class(es) N.A. Packing group N.A. Environmental hazards ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) N.A. Special precautions in connection with transport or conveyance N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations
(HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:
None.

DSL inventory - Domestic substances list

All the components are listed in the DSL...

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

ammonia ...% is listed in TSCA Section 8b

LWM054/1 Page n. 7 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b 2-metil-2H-isotiazol-3-one is listed in TSCA Section 12b, Section 8b.
	eral regulations
SAF	RA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substances listed. Section 304 – Hazardous substances: ammonia%.
CEF	Section 313 – Toxic chemical list: ammonia%. RCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA: ammonia% - Reportable quantity: 1000 pounds.
CAA	Reportable quantity for mixture: 693481.276 pounds. - Clean Air Act CAA listed substances:
CW	None. A - Clean Water Act CWA listed substances: ammonia% is listed in CWA Section 311.
	e specific regulations
Cali	fornia Proposition 65 Substance(s) listed under California Proposition 65: None.
Mas	sachusetts Right to know Substance(s) listed under Massachusetts Right to know: ammonia%.
New	/ Jersey Right to know Substance(s) listed under New Jersey Right to know: ammonia%.
Pen	nsylvania Right to know Substance(s) listed under Pennsylvania Right to know: ammonia%.
Volatile Organic of	compounds - VOCs = 3.84 % compounds - VOCs = 39.54 g/l ostances = 0.00 %

Organic Carbon - C = 0.02

16. Other information

Full text of phrases referred to in Section 3:

- H314 Causes severe skin burns and eye damage.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H410 Very toxic to aquatic life with long lasting effects.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H331 Toxic if inhaled.
- H315 Causes skin irritation.
- H302 Harmful if swallowed.
- H330 Fatal if inhaled.

Safety Data Sheet dated 7/3/2019, version 1

LWM054/1 Page n. 8 of 9

LWM054 IDROFIX 20 Polivalente acqua interno - Clear WB self-seal interior

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of
	Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical
	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"
	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average