



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

Safety Data Sheet dated 7/23/2020, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

Other means of identification:

Trade code:

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Richelieu America Itd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Distributor:

Richelieu America Itd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NÚOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

Warning, Skin Sens. 1, May cause an allergic skin reaction.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see ... On this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



•

LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus



HMIS rating:



3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances N.A. Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number		Classification
>= 15% - < 20%	Titanium Dioxide	CAS: EC: REACH No.:	13463-67-7 236-675-5 01- 2119489379-17	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
>= 5% - < 7%	2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	Index number: CAS: EC: REACH No.:	603-014-00-0 111-76-2 203-905-0 01- 2119475108-36	↑ A.3/2A Eye Irrit. 2A H319 B.6/4 Flam. Liq. 4 H227 ↑ A.2/2 Skin Irrit. 2 H315 ↑ A.1/4/Oral Acute Tox. 4 H302 ↑ A.1/4/Dermal Acute Tox. 4 H312 ↑ A.1/4/Inhal Acute Tox. 4 H332
483 ppm	2,4,7,9-tetramethyldec-5-yne- 4,7-diol	CAS: EC: REACH No.:	126-86-3 204-809-1 01- 2119954390-39	 ♠ A.3/1 Eye Dam. 1 H318 ♠ A.4.2/1B Skin Sens. 1B H317 US-HAE/C3 Aquatic Chronic 3 H412
198 ppm	1,2-benzisothiazol-3(2H)- one; 1,2-benzisothiazolin-3- one	Index number: CAS: EC: REACH No.:	613-088-00-6 2634-33-5 220-120-9 01- 2120761540-60	↑ A.1/4/Oral Acute Tox. 4 H302 ↑ A.2/2 Skin Irrit. 2 H315 ↑ A.3/1 Eye Dam. 1 H318 ↑ A.4.2/1 Skin Sens. 1 H317 ↓ US-HAE/A1 Aquatic Acute 1 H400 ↓ US-HAE/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 0,05%: Skin Sens. 1 H317
34 ppm	ammonia%	Index number: CAS: EC: REACH No.:	007-001-01-2 1336-21-6 215-647-6 01- 2119982985-14	A.2/1B Skin Corr. 1B H314 A.8/3 STOT SE 3 H335 US-HAE/A1 Aquatic Acute 1 H400 Specific Concentration Limits: C >= 5%: STOT SE 3 H335
18 ppm	2-methyl-2H-isothiazol-3-one	CAS: EC:	2682-20-4 220-239-6	 ♦ A.1/2/Inhal Acute Tox. 2 H330 ♦ A.1/3/Dermal Acute Tox. 3 H311



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

noi p	ius			
		REACH No.:	01- 2120764690-50	A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 Specific Concentration Limits: C >= 0,0015%: Skin Sens. 1 H317
8 ppm	Decamethylcyclopentasiloxan e (D5)	CAS: EC: REACH No.:	541-02-06 208-764-9 01- 2119511367-43	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
8 ppm	octamethylcyclotetrasiloxane (D4)	Index number: CAS: EC: REACH No.:	014-018-00-1 556-67-2 209-136-7 01- 2119529238-36	 ♦ B.6/3 Flam. Liq. 3 H226 ♦ A.7/2 Repr. 2 H361 US-HAE/C4 Aquatic Chronic 4 H413
8 ppm	Dodecamethylcyclohexasiloxa ne (D6)	CAS: EC: REACH No.:	540-97-6 208-762-8 01- 2119517435-42	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
2 ppm	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4+CAS 2682-20-4)	Index number: CAS: REACH No.:	613-167-00-5 55965-84-9 01- 2120764691-48	A.2/1B Skin Corr. 1B H314 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/2/Inhal Acute Tox. 2 H330 Specific Concentration Limits: C >= 0,6%: Skin Corr. 1B H314 0,06% <= C < 0.6%: Skin Irrit. 2 H315 0,06% <= C < 0.6%: Eye Irrit. 2A H319 C >= 0,0015%: Skin Sens. 1 H317

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

LWT654/1

Page n. 3 of 10



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

Explosive properties: N.D. in volume Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Titanium Dioxide - CAS: 13463-67-7

ACGIH - TWA(8h): 10 mg/m3 - Notes: A4 - LRT irr

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

EU - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

ammonia ...% - CAS: 1336-21-6

ACGIH - TWA: 18 mg/m3, 25 ppm - STEL: 27 mg/m3, 35 ppm Decamethylcyclopentasiloxane (D5) - CAS: 541-02-06

ACGIH - TWA(8h): 10 ppm

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

ÁCGIH - TWA(8h): 123 mg/m3, 10 ppm

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no.

220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3

DNEL Exposure Limit Values

Titanium Dioxide - CAS: 13463-67-7

Worker Industry: 10 mg/m3 - Worker Professional: 10 mg/m3 - Exposure: Human Inhalation - Frequency: Long

Term, local effects

Consumer: 700 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Worker Industry: 125 mg/kg - Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 98 mg/m3 - Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects 2,4,7,9-tetramethyldec-5-yne-4,7-diol - CAS: 126-86-3

Worker Industry: 0.5 - Worker Professional: 0.5 mg/kg - Consumer: 0.25 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Industry: 1.76 - Worker Professional: 1.76 mg/m3 - Consumer: 0.43 mg/m3 - Exposure: Human

Inhalation - Frequency: Long Term, systemic effects

ammonia ...% - CAS: 1336-21-6



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term. systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 36 mg/m3 - Worker Professional: 36 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 14 mg/m3 - Worker Professional: 14 mg/m3 - Consumer: 2.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Worker Industry: 73 mg/m3 - Worker Professional: 73 mg/m3 - Consumer: 13 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects PNEC Exposure Limit Values Titanium Dioxide - CAS: 13463-67-7 Target: Fresh Water - Value: 0.184 mg/l Target: Marine water - Value: 0.0184 mg/l Target: Intermittent emission - Value: 0.61 mg/l Target: Freshwater sediments - Value: 1000 mg/kg Target: Marine water sediments - Value: 100 mg/kg
Target: Microorganisms in sewage treatments - Value: 100 mg/l Target: Soil (agricultural) - Value: 100 mg/kg Target: Food chain - Value: 1667 mg/kg 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 Target: Fresh Water - Value: 8.8 mg/l Target: Marine water - Value: 0.88 mg/l Target: Intermittent emission - Value: 9.1 mg/l
Target: Freshwater sediments - Value: 8.14 mg/kg Target: Marine water sediments - Value: 3.46 mg/kg Target: Microorganisms in sewage treatments - Value: 463 mg/l Target: Food chain - Value: 20 mg/kg Target: Soil (agricultural) - Value: 2.33 mg/kg 2,4,7,9-tetramethyldec-5-yne-4,7-diol - CAS: 126-86-3 Target: Fresh Water - Value: 0.04 mg/l Target: Marine water - Value: 0.004 mg/l

Target: Freshwater sediments - Value: 0.32 mg/kg Target: Marine water sediments - Value: 0.032 mg/kg Target: Microorganisms in sewage treatments - Value: 7 mg/l

Target: Soil (agricultural) - Value: 0.028 mg/kg

ammonia ...% - CAS: 1336-21-6

Target: Fresh Water - Value: 0.0011 mg/l Target: Marine water - Value: 0.0011 mg/l

Target: Intermittent emission - Value: 0.0068 mg/l

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Target: Fresh Water - Value: 0.00044 mg/l Target: Marine water - Value: 0.000044 mg/l

Target: Freshwater sediments - Value: 0.128 mg/kg Target: Marine water sediments - Value: 0.013 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/kg

Target: Soil (agricultural) - Value: 0.136 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374) Respiratory protection:

Not needed for normal use.

Thermal Hazards



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:

Odour:

Odour threshold:

PH:

Melting point / freezing point:

Initial boiling point and boiling range:

Solid/gas flammability:

white fluid typical

N.D.

8.5

N.D. °C

> 100 °C

N.A.

Upper/lower flammability or explosive limits: N.D.

Vapour density: Flash point: N.A. °C Evaporation rate: N.D. Vapour pressure: N.D. (20 °C) Relative density: 1.110- 1.130 Solubility in water: miscible Solubility in oil: N.D. Partition coefficient (n-octanol/water): N.D. Auto-ignition temperature: N.D. °C N.D. °C Decomposition temperature: Viscosity: N.D. Miscibility: N.D. Fat Solubility: N.D. Conductivity: N.D. Substance Groups relevant properties

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product



.

LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

```
h) STOT-single exposure
                Not classified
                No data available for the product
        i) STOT-repeated exposure
                Not classified
                No data available for the product
        j) aspiration hazard
                Not classified
                No data available for the product
Toxicological information of the main substances found in the product:
        Titanium Dioxide - CAS: 13463-67-7
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425
                Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
                Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h
        2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat = 1300 mg/kg
                Test: LC50 - Route: Inhalation - Species: Rat > 523 Ppm - Duration: 4h
                Test: LC50 - Route: Skin - Species: Rabbit > 435 mg/kg
        2,4,7,9-tetramethyldec-5-yne-4,7-diol - CAS: 126-86-3
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
        1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg
                Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg
        2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg
        octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
        a) acute toxicity:
                Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg
                Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h
                Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg
        mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no.
        220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
        a) acute toxicity:
                Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h
                Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg
        2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
                The product is harmful if inaled, swallowed or absorbed through skin. Repeated or extended exposures cause
                headache,drowsiness,weakness, stuttering,blurred vision,urinary albumin,kidneys demages,liver enlargement
                and haemolysis.
Substance(s) listed on the NTP report on Carcinogens:
        None.
Substance(s) listed on the IARC Monographs:
        Titanium Dioxide - Group 2B
        2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3.
Substance(s) listed as OSHA Carcinogen(s):
       None.
Substance(s) listed as NIOSH Carcinogen(s):
        Titanium Dioxide.
```

12. ECOLOGICAL INFORMATION

```
Ecotoxicity
Adopt good working practices, so that the product is not released into the environment.

IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus
Not classified for environmental hazards
No data available for the product

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Algae = 623 mg/l - Duration h: 72 - Notes: OECD 201
Endpoint: EC50 - Species: Daphnia = 1550 mg/l - Duration h: 48 - Notes: OECD 202
Endpoint: LC50 - Species: Fish = 1474 mg/l - Duration h: 96 - Notes: OECD 203
b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 d
```

Endpoint: NOEC - Species: Algae = 62.5 mg/l - Duration h: 72



.

LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

```
2,4,7,9-tetramethyldec-5-yne-4,7-diol - CAS: 126-86-3
        a) Aquatic acute toxicity:
                 Endpoint: EC50 - Species: Algae = 15 mg/l - Duration h: 72
                 Endpoint: EC50 - Species: Daphnia = 91 mg/l - Duration h: 48
                 Endpoint: LC50 - Species: Fish = 36 mg/l - Duration h: 96
                 Endpoint: LC50 - Species: Fish = 42 mg/l - Duration h: 24
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
        a) Aquatic acute toxicity:
                 Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
                 Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
                 Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
        b) Aquatic chronic toxicity:
                 Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
                 Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
ammonia ...% - CAS: 1336-21-6
        a) Aquatic acute toxicity:
                 Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48
                 Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96
        b) Aquatic chronic toxicity:
                 Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96
Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d 2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4
        a) Aquatic acute toxicity:
                 Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96
                 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)
(CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
        a) Aquatic acute toxicity:
                 Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72
                 Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48
                 Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96
        b) Aquatic chronic toxicity:
                Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211
                 Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210
Persistence and degradability
        2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
Biodegradability: Readily biodegradable - Duration h: 28 days - %: 90.4 - Notes: OECD 301B
        1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
                 Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD
        octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
                 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310
Bioaccumulative potential
        Decamethylcyclopentasiloxane (D5) - CAS: 541-02-06
                 Bioaccumulation: Bioaccumulative
        octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
                 Bioaccumulation: Bioaccumulative
        Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
                 Bioaccumulation: Bioaccumulative
Mobility in soil
        N.A.
Other adverse effects
        None
```

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

```
UN number
Not classified as dangerous in the meaning of transport regulations.
UN proper shipping name
N.A.
Transport hazard class(es)
```



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

N.A. Packing group Ň.A.

Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: Nο

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Special precautions

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

Titanium Dioxide is listed in TSCA Section 8b

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 8b, Section 8d HSDR

2,4,7,9-tetramethyldec-5-yne-4,7-diol is listed in TSCA Section 8b

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b ammonia ...% is listed in TSCA Section 8b

2-methyl-2H-isothiazol-3-one is listed in TSCA Section 12b, Section 8b

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b,

Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: ammonia ...%.

Section 313 - Toxic chemical list: ammonia ...%.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: ammonia ...% - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 28985507.25 pounds.

CAA - Clean Air Act

CAA listed substances:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in CAA Section 111.

CWA - Clean Water Act

CWA listed substances:

ammonia ...% is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Titanium Dioxide - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Titanium Dioxide

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

ammonia ...%

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Titanium Dioxide

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

ammonia ...%.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Titanium Dioxide

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

ammonia ...%.

Volatile Organic compounds - VOCs = 8.06 %

Volatile Organic compounds - VOCs = 91.10 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.05

16. OTHER INFORMATION

LWT654/1

Page n. 9 of 10



LWT654 IDROLACK 20 Finitura bianca interno PLUS - White WB top coat interior plus

Full text of phrases referred to in Section 3:

H319 Causes serious eye irritation.

H227 Combustible liquid.

H315 Causes skin irritation.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H330 Fatal if inhaled.

H311 Toxic in contact with skin.

H301 Toxic if swallowed.

H410 Very toxic to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H361 Suspected of damaging fertility or the unborn child.

H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 7/23/2020, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

Classification, Labeling, Packaging. CLP:

DNEL: Derived No Effect Level

EINECS: European Inventory of Existing Commercial Chemical Substances. GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

International Maritime Code for Dangerous Goods. IMDG: INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health National Toxicology Program
Occupational Safety and Health Administration. NTP:

OSHA: PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. Threshold Limiting Value. TLV: TWA: Time-weighted average