

LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

Safety Data Sheet dated 3/26/2020, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name: CONVERTER IDRO 10 Opaco interni - CONV for interior matt

WB

Other means of identification

Trade code: LXV405
Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Converter for paints

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00) Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

The product is not classified as dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements

The product is not classified as dangerous according to WHMIS 2015.

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/Information on ingredients

LXV405/1

Page n. 1 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

Substances N.A. Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number		Classification
>= 1% - < 5%	2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	Index number: CAS: EC: REACH No.:	603-014-00-0 111-76-2 203-905-0 01- 2119475108 -36	 ♠ A.2/2 Skin Irrit. 2 H315 ♠ A.3/2A Eye Irrit. 2A H319 B.6/4 Flam. Liq. 4 H227 ♠ A.1/4/Oral Acute Tox. 4 H302 ♠ A.1/4/Dermal Acute Tox. 4 H312 ♠ A.1/4/Inhal Acute Tox. 4 H332
181 ppm	1,2-benzisothiazol- 3(2H)-one; 1,2- benzisothiazolin-3-one	Index number: CAS: EC: REACH No.:	2634-33-5 220-120-9	 ♠ A.1/4/Oral Acute Tox. 4 H302 ♠ A.2/2 Skin Irrit. 2 H315 ♠ A.4.2/1 Skin Sens. 1 H317 ♠ A.3/1 Eye Dam. 1 H318 ♠ CAN-HAE/A1 Aquatic Acute 1 H400 ♠ CAN-HAE/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 0,05%: Skin Sens. 1 H317
25 ppm	octamethylcyclotetrasilo xane (D4)	Index number: CAS: EC: REACH No.:	556-67-2 209-136-7	 ♦ B.6/3 Flam. Liq. 3 H226 ♦ A.7/2 Repr. 2 H361 CAN-HAE/C4 Aquatic Chronic 4 H413
25 ppm	Decamethylcyclopentas iloxane (D5)	CAS: EC: REACH No.:	541-02-06 208-764-9 01- 2119511367 -43	The product is not classified as dangerous according to WHMIS 2015.
25 ppm	Dodecamethylcyclohex asiloxane (D6)	CAS: EC: REACH No.:	540-97-6 208-762-8 01- 2119517435 -42	The product is not classified as dangerous according to WHMIS 2015.
7 ppm	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: CAS: REACH No.:	55965-84-9	 A.2/1B Skin Corr. 1B H314 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/2/Inhal Acute Tox. 2 H330 Specific Concentration Limits: C >= 0,0015%: Skin Sens. 1 H317



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

				0,06% <= C < 0.6%: Skin Irrit. 2 H315 C >= 0,6%: Skin Corr. 1B H314
4 ppm	2-methyl-2H-isothiazol- 3-one	CAS: EC: REACH No.:	2682-20-4 220-239-6 01- 2120764690 -50	 ♠ A.1/2/Inhal Acute Tox. 2 H330 ♠ A.1/3/Dermal Acute Tox. 3 H311 ♠ A.1/3/Oral Acute Tox. 3 H301 ♠ A.2/1B Skin Corr. 1B H314 ♠ A.4.2/1A Skin Sens. 1A H317 ♠ CAN-HAE/A1 Aquatic Acute 1 H400 ♠ CAN-HAE/C1 Aquatic Chronic 1 H410 Specific Concentration Limits: C >= 0,0015%: Skin Sens. 1 H317

The actual concentration of the components listed above is withheld as a trade secret.

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into

draine

Move undamaged containers from immediate hazard area if it can be done safely.

LXV405/1

Page n. 3 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

EU - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

ACGIH - TWA(8h): 123 mg/m3, 10 ppm

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-06

ACGIH - TWA(8h): 10 ppm

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS:

55965-84-9

TLV TWA - 0,05 mg/m3

TLV STEL - 0,23 mg/m3

DNEL Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Worker Industry: 125 mg/kg - Worker Professional: 125 mg/kg - Consumer: 75 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 98 mg/m3 - Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Worker Industry: 73 mg/m3 - Worker Professional: 73 mg/m3 - Consumer: 13 mg/m3 -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -

Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

Target: Marine water - Value: 0.88 mg/l

Target: Intermittent emission - Value: 9.1 mg/l Target: Freshwater sediments - Value: 8.14 mg/kg Target: Marine water sediments - Value: 3.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 463 mg/l

Target: Food chain - Value: 20 mg/kg

Target: Soil (agricultural) - Value: 2.33 mg/kg

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Target: Fresh Water - Value: 0.00044 mg/l Target: Marine water - Value: 0.000044 mg/l

Target: Freshwater sediments - Value: 0.128 mg/kg Target: Marine water sediments - Value: 0.013 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/kg

Target: Soil (agricultural) - Value: 0.136 mg/kg

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Chemical resistant gloves (EN374).

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour: opalescent fluid

Odour: typical
Odour threshold: N.D.
pH: 8.5
Melting point / freezing point: N.D. °C

Initial boiling point and boiling range: > 100 °C

Flash point: > 93 °C
Evaporation rate: N.D.
Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.D.

Vapour pressure: N.D. (20 °C)

Vapour density: > 1

Relative density:

Solubility in water:

Solubility in oil:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

N.D. -1.030

miscible
partial
N.D. °C
N.D. °C
N.D. °C
N.D. °C
N.D. °C

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

LXV405/1

Page n. 5 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

Not classified

No data available for the product

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

Not classified

No data available for the product

i) STOT-repeated exposure

Not classified

No data available for the product

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1300 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 523 Ppm - Duration: 4h

Test: LC50 - Route: Skin - Species: Rabbit > 435 mg/kg

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

LXV405/1 Page n. 6 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h

Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg

2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2 The product is harmful if inaled, swallowed or absorbed through skin. Repeated or extended exposures cause headache drowsiness weakness, stuttering blurred vision, urinary albumin, kidneys demages, liver enlargement and haemolysis.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment. CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

Not classified for environmental hazards

No data available for the product

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 623 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: EC50 - Species: Daphnia = 1550 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: LC50 - Species: Fish = 1474 mg/l - Duration h: 96 - Notes: OECD 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 d Endpoint: NOEC - Species: Algae = 62.5 mg/l - Duration h: 72

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d

Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201

Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211

Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210

2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48

Persistence and degradability

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 90.4 - Notes: OECD 301B

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310

Bioaccumulative potential

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Bioaccumulation: Bioaccumulative

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-06

Bioaccumulation: Bioaccumulative

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Bioaccumulation: Bioaccumulative

Mobility in soil

N.A

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

Ν.Α.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A

Special precautions in connection with transport or conveyance

N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in NPRI Part 5.

LXV405/1 Page n. 8 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 8b, Section 8d HSDR

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b

2-methyl-2H-isothiazol-3-one is listed in TSCA Section 12b, Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 - Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act No substances listed.

CAA - Clean Air Act

CAA listed substances:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in CAA Section 111.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Volatile Organic compounds - VOCs = 5.67 % Volatile Organic compounds - VOCs = 58.42 g/l Volatile CMR substances = 0.00 % Organic Carbon - C = 0.03

16. Other information

Full text of phrases referred to in Section 3:

LXV405/1

Page n. 9 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H227 Combustible liquid. H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H361 Suspected of damaging fertility or the unborn child. H413 May cause long lasting harmful effects to aquatic life.

H314 Causes severe skin burns and eye damage. H410 Very toxic to aquatic life with long lasting effects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H330 Fatal if inhaled.

Safety Data Sheet dated 3/26/2020, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

LXV405/1

Page n. 10 of 11



LXV405 CONVERTER IDRO 10 Opaco interni - CONV for interior matt WB

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average