

Description

Cleaning Agent

Type of Adhesive: Monocyclic Hydrocarbon

Field of Application: Cleaning Agent

Typical Technical Data:

Color: Clear Liquid

Application Temperature: Room Temperature

Odor: Strong citrus odor

Properties:

TECHNOMELT PUR CLEANER 3030 is recommended as a surface cleaning agent in areas where most types of water-based and/or hot melt adhesives are used. TECHNOMELT PUR CLEANER 3030 could also be used to soak machine parts. TECHNOMELT PUR CLEANER 3030 should not be heated. TECHNOMELT PUR CLEANER 3030 is classified by the FDA as GRAS (Generally Recognized As Safe).

Handling and Application:

90-3030 is also recommended for overnight soaking of equipment parts and filters.

Precautions:

It is not recommended that 90-3030 be diluted with water. All precautions listed in the MSDS should be taken when handling this cleaning agent.

Storage Conditions:

Keep container closed when not in use. Store at temperatures below 115°F. Keep away from open flames.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.