# Safety Data Sheet



Revision Number: 001.0

# **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name:LOCTITE UR 10 400 ML BTLProduct type:Polyurethane adhesiveRestriction of Use:This product is for industrial use only.Company address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

IDH number:

2379343

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
	DIFFICULTIES IF INHALED.
	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED
	EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)

#### **Precautionary Statements**

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.
Response:	IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methylenebis(phenylisocyanate)	101-68-8	5 - 10
Isocyanic acid, polymethylene ester	9016-87-9	5 - 10
2,2'-dimorpholinyldiethyl ether	6425-39-4	0.1 - 1
Isocyanate terminated polyurethane	Proprietary	80 - 90

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.		
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Immediately remove soiled or soaked clothing. Get medical attention.		
Eye contact:	Check for and remove any contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.		
Ingestion:	If material is ingested, immediately contact a physician or poison control center. Keep individual calm. DO NOT induce vomiting unless directed to do so by medical personnel.		
Symptoms:	See Section 11.		
Notes to physician:	Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or sensitization should be excluded from working with isocyanates.		

# 5. FIRE FIGHTING MEASURES Extinguishing media: Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide. Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Keep unnecessary personnel away. Unusual fire or explosion hazards: Sealed containers at elevated temperatures or contaminated with water may rupture explosively. In case of fire, keep containers cool with water spray.

#### Hazardous combustion products:

Irritating and toxic gases or fumes may be released during a fire. Isocyanate vapors. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Hydrogen cyanide.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not empty into drains / surface water / ground water. Follow all local, state, federal and provincial regulations for disposal.
Clean-up methods:	Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. For minor spills, absorb isocyanates with sawdust or other absorbent, shovel into suitable unsealed containers, transport to well ventilated area (outside) and treat with neutralizing solution: mixture of 80% water and 20% non-ionic surfactant Tergitol TMN-10; or 90% water, 3-8% concentrated ammonia and 2% detergent. Large quantities may be pumped into closed, but not sealed containers for disposal. If temporary control of isocyanate vapor is required, a blanket of protein foam (available at most fire departments) may be placed over spill.

#### 7. HANDLING AND STORAGE

Handling:

Storage:

Use only in well-ventilated areas. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Wear suitable protective clothing, safety glasses and gloves.

Do not let moisture contaminate this material. Product reacts with water to release carbon dioxide, which could build up pressure in closed containers and lead to bursting. Do not reseal if moisture contamination is suspected. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from direct sunlight.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methylenebis(phenylisocyanate)	0.005 ppm TWA	0.02 ppm (0.2 mg/m3) Ceiling	None	None
Isocyanic acid, polymethylene ester	None	None	None	None
2,2'-dimorpholinyldiethyl ether	None	None	None	None
Isocyanate terminated polyurethane	None	None	None	None

**Engineering controls:** 

Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination. Monitoring of airborne isocyanates in the breathing zone of individuals should become part of the overall employee exposure characterization program. Once a person is diagnosed as sensitized to an isocyanate, no further exposure can be permitted.

Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). A positive pressure, supplied-air respirator or a self-contained breathing apparatus is recommended when: airborne concentrations of isocyanate are known to exceed 0.005 ppm; operations are performed in a confined space or area with limited ventilation; material is heated or sprayed. Do not inhale vapors and fumes. Observe OSHA regulations for respirator use (29 CFR 1910.134).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. The workplace should be equipped with an emergency shower and eye-rinsing facility.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Clear

Physical state: Color: Odor: Odor threshold: pH: . Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: Decomposition temperature:

Odorless Not available. Not applicable Not available. Not available. Not available. 1.05 Not available. > 180 °C (> 356°F) Not available. Not available. Not available. Not applicable Not available. Reacts slowly with water to liberate carbon dioxide gas. Not available. 0% Not available. Not available.

#### **10. STABILITY AND REACTIVITY**

Stability:	Stable under recommended storage conditions.
Hazardous reactions:	Exothermic. Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen cyanide. Isocyanate vapors
Incompatible materials:	Water. Moisture. Humid air and/or water will produce carbon dioxide which will pressurize the container. Amines. Alcohols. Ammonia. Strong bases.
Reactivity:	Not available.
Conditions to avoid:	Avoid moisture. Container can be pressurised by carbon dioxide due to reaction with humid air and/or water. Protect from direct sunlight. Excessive heat.

## **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. This product may cause sensitization by inhalation and skin contact. Overexposure to isocyanates may cause burning sensation of respiratory tract, cough, shallow breathing, burning sensation, tightness in chest, reduced lung function. As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage.
Skin contact:	Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons. Isocyanates react with skin protein and moisture and can cause irritation which may include the following symptoms: reddening, swelling, rash, scaling or blistering.
Eye contact:	Liquid or vapor can cause moderate to severe irritation. Symptoms can include irritation, redness, scratching of the cornea, and tearing. Conjunctivitis.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects Irritant, Respiratory, Allergen	
Methylenebis(phenylisocyanate)	Inhalation LC50 (Rat, 4 h) = $0.38 \text{ mg/l}$ Inhalation LC50 (Rat, 4 h) = $0.369 \text{ mg/l}$		
Isocyanic acid, polymethylenepolyphenylene ester	None	Allergen, Irritant, Kidney, Liver, Respiratory	
2,2'-dimorpholinyldiethyl ether	None	No Records	
Isocyanate terminated polyurethane	None	No Data	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methylenebis(phenylisocyanate)	No	No	No
Isocyanic acid, polymethylenepolyphenylene ester	No	No	No
2,2'-dimorpholinyldiethyl ether	No	No	No
Isocyanate terminated polyurethane	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information:

Do not empty into drains, soil or bodies of water.

# **13. DISPOSAL CONSIDERATIONS**

#### Information provided is for unused product only.

Recommended method of disposal:	Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.
Hazardous waste number:	To the best of our knowledge, this product is not listed nor does it meet the criteria of a hazardous waste if discarded in its purchased form. However, under RCRA, it is the responsibility of the user to determine at the time of disposal whether a product meets any of the RCRA hazardous waste criteria. This is because product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics under the new Toxicity Characteristics Leaching Procedure (TCLP) 40 Code of Federal Regulations 261.20-24.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (4	49 CFR)
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

## **15. REGULATORY INFORMATION**

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health, Reactive This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methylenebis(phenylisocyanate) (CAS# 101-68-8). Isocyanic acid, polymethylenepolyphenylene ester (CAS# 9016-87-9).
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: C. Poulsen, Regulatory Affairs

Issue date: 03/23/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.