







Section 1: Product and Company Identification

RPM Wood Finishes Group, Inc. Company Phone number: (800) 522-8266

P.O. Box 22000 CHEMTREC: (800) 424-9300 International: 703-527-3887 (collect)

Hickory, NC 28603 EHS Review/Issue Date: 04/16/2014

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Product Code: ACAB, ACPA, M101-0229

Section 2: Hazards Identification

EMERGENCY OVERVIEW

Appearance: Colored Liquid Odor: Moderately Strong Alcohol

Principal Hazards: DANGER! Extremely Flammable.

Causes eye, skin, nose and throat irritation. Harmful or fatal if swallowed. Harmful if inhaled. Vapor harmful.

Potential Health Effects: See Section 11 for more information.

Primary Routes of Exposure:

Eye Contact:

Product may cause eye damage; signs and symptoms may include burns, vision impairment, permanent corneal damage and/or soft tissue damage. These effects may be delayed.

Ingestion:

Product if ingested may cause damage (including burns, scarring, and ulcerization) to mouth, throat, stomach, and digestive and central nervous systems. Signs and symptoms may include headache, drowsiness, dizziness, swelling, abdominal discomfort, burning sensation, shock or collapse, convulsions and/or bleeding. These effects may be delayed. Post-ingestion vomitous in the lungs may cause chemical pneumonia.

Skin Contact:

Product may cause skin damage; signs and symptoms may include blistering, burns and/or possible scarring. May be harmful if absorbed through the skin.

Inhalation:

Product if inhaled may cause severe irritation or damage (including but not limited to burns, scarring, and ulcerization) to respiratory tract and central nervous system. Signs and symptoms may include weakness, headache, drowsiness, dizziness, swelling, abdominal discomfort, burning sensation, shock or collapse, convulsions, breathing difficulties, nasal perforation, ulceration, heart damage, blindness, bleeding and/or death. Serious risk of suffocation when in confined area. These effects may be delayed. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EHS Review/Issue Date: 04/16/2014 Page 1 of 9

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Target Organs: blood effects

Carcinogenicity: This product contains carcinogens or potential carcinogens as listed by IARC or NTP.

Hazardous Listing: Components of this product are considered hazardous per the OSHA Hazard Communication Standard (29 CFR

1910.1200).

Section 3: Composition/Information on Ingredients

Chemical	CAS	Percent Composition
acetone	67-64-1	20 - 30
propane	74-98-6	10 - 20
isobutyl acetate	110-19-0	1 - 10
ethyl acetate	141-78-6	1 - 10
n-butyl acetate	123-86-4	1 - 10
ethanol	64-17-5	1 - 10
isobutane	75-28-5	1 - 10
toluene	108-88-3	1 - 10
cellulose nitrate, cellulose ester	9004-70-0	1 - 10
alkyd resin	proprietary	1 - 10
isopropanol	67-63-0	1 - 10
pm acetate	108-65-6	1 - 10
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0	1 - 10
ethylbenzene	100-41-4	< 1
carbon black	1333-86-4	< 0.1
benzene	71-43-2	< 0.1
aniline	62-53-3	< 0.1

Section 4: First Aid Measures

Eye Contact:

If exposure occurs, flush the affected eye for at least 20 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention immediately after flushing.

EHS Review/Issue Date: 04/16/2014 Page 2 of 9

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Ingestion:

Do not induce vomiting. Dilute with water or milk. Never give fluids if the victim is unconscious or having convulsions. Seek medical attention immediately. Contact Poison Control Center immediately.

Skin Contact:

If exposure occurs, flush the affected area thoroughly with water for at least 15 minutes. Destroy contaminated clothing and shoes. Seek medical attention immediately.

Inhalation:

Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Seek medical attention immediately.

Section 5: Fire Fighting Measures

Extinguishing Media:

This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

Products of Combustion:

Protection of Firefighters / Explosion Hazards:

Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

Section 6: Accidental Release Measures

EHS Review/Issue Date:04/16/2014
File: IACAB MSDS ENGUSA 005.pdf

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Section 7: Handling and Storage

Handling:

Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not store above 120°F, or in direct sunlight. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Storage:

Section 8: Exposure / Personal Protection

OSHA 29 CFR 1910.1000 Air Contaminants – Tables:

Chemical	CAS	Z-1 PEL (units as noted)	Z-2 PEL (PPM)	Z-3 Status	Specifically Regulated see:	ACGIH TLV (units as noted)	
acetone	67-64-1	2400 MGM3 (1000 PPM)				500 PPM	
propane	74-98-6	1800 MGM3 (1000 PPM)					
isobutyl acetate	110-19-0	700 MGM3 (150 PPM)				150 PPM	
ethyl acetate	141-78-6	1400 MGM3 (400 PPM)				400 PPM	
n-butyl acetate	123-86-4	710 MGM3 (150 PPM)				150 PPM	
ethanol	64-17-5	1900 MGM3 (1000 PPM)				1000 PPM	
isobutane	75-28-5					1000 PPM	
toluene	108-88-3		200 PPM			20 PPM	
cellulose nitrate, cellulose ester	9004-70-0						
alkyd resin	proprietary						
isopropanol	67-63-0	980 MGM3 (400 PPM)				200 PPM	
pm acetate	108-65-6						
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0						
ethylbenzene	100-41-4	435 MGM3 (100 PPM)				100 PPM	
carbon black	1333-86-4	3.5 MGM3				3.5 MGM3	
benzene	71-43-2		10 PPM		29 CFR 1910.1028	0.5 PPM	
aniline	62-53-3	19 MGM3 (5 PPM)				2 PPM	

EHS Review/Issue Date: 04/16/2014 Page 4 of 9

Product Name: AEROSOL CAN AUTUMIN BLUSH/MOHAWK BROWN MAHOGANY							
	_						

Engineering	Controls:
-------------	-----------

Eye / Face Protection:

Skin Protection:

Respiratory Protection:

A NIOSH-approved air-purifying respirator with the appropriate cartridge may be appropriate under certain circumstances where airborne concentrations are expected to exceed permissible exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

General Hygiene Considerations:

Section 9: Physical and Chemical Properties

Physical State: Colored Liquid

Odor: Moderately Strong Alcohol

Odor Threshold: Not determined. pH: Not determined. **Freezing Point:** Not determined. **Boiling Point:** Not determined. -144 (CALC.) Flash Point (°F): **Evaporation Rate:** Not determined. Flammability (solid, gas): Not determined. Not determined. **Upper Flammability Limit: Lower Flammability Limit:** Not determined. **Vapor Pressure:** Not determined. **Vapor Density:** Not determined.

EHS Review/Issue Date: 04/16/2014

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Specific Gravity: 0.76

Weight per Gallon (lbs): 6.35

Solubility (water):

Partition Coefficient (n-octanol/water):

Not determined.

Auto-ignition Temperature:

Not determined.

Coating VOC g/l: 662.65
Coating VOC lbs/gal: 5.52
Material VOC g/l: 495.04
Material VOC lbs/gal: 4.12
Solids VOL%: 4.96
Solids WT %: 8.55

Contains Non-Photochemically Reactive Solvent.

VOC data per US EPA guidelines. Some states and localities have guidelines more stringent than federal regulations. Aerosol coating product category codes and applicable reactivity limits are displayed on product labels per 40 CFR 59.507.

Section 10: Stability and Reactivity

Sta	bil	litv	:
Sta	DI	lity	:

Conditions to Avoid/Incompatible Materials:

Hazardous Decomposition Products:

EHS Review/Issue Date: 04/16/2014
File: IACAB_MSDS_ENGUSA_005.pdf

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Section 11: Toxicology Information

Chemical	CAS	IARC	NTP
acetone	67-64-1		
propane	74-98-6		
isobutyl acetate	110-19-0		
ethyl acetate	141-78-6		
n-butyl acetate	123-86-4		
ethanol	64-17-5	*	*
isobutane	75-28-5		
toluene	108-88-3		
cellulose nitrate, cellulose ester	9004-70-0		
alkyd resin	proprietary		
isopropanol	67-63-0		
pm acetate	108-65-6		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0		
ethylbenzene	100-41-4		
carbon black	1333-86-4		
benzene	71-43-2	*	*
aniline	62-53-3		

Toxicological evaluation of this product as a whole has not been performed. Individual components that are potential or known carcinogens are listed above.

Section 12: Ecological Information

EHS Review/Issue Date: 04/16/2014

Product Name: AEROSOL CAN AUTUMN BLUSH/MOHAWK BROWN MAHOGANY

Section 13: Disposal Considerations

Section 14: Transportation Information

DOT Basic description: UN1950, AEROSOLS, FLAMMABLE, 2.1

See 49 CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

Section 15: Regulatory Information

Chemical Name	CAS	CERCLA	CERCLA RQ	EPCRA EHS	EPCRA TPQ	SARA 313	TSCA	DSL	EINECS	Proposition 65	WHMIS
acetone	67-64-1	*	5000 LBS				*	*	*		*
propane	74-98-6						*	*	*		
isobutyl acetate	110-19-0	*	5000 LBS				*	*	*		*
ethyl acetate	141-78-6	*	5000 LBS				*	*	*		*
n-butyl acetate	123-86-4	*	5000 LBS				*	*	*		*
ethanol	64-17-5	*	100 LBS				*	*	*		*
isobutane	75-28-5						*	*	*		
toluene	108-88-3	*	1000 LBS			*	*	*	*	*	*
cellulose nitrate, cellulose ester	9004-70-0	*	100 LBS				*	*			
alkyd resin	proprietary										
isopropanol	67-63-0					*	*	*	*		*
pm acetate	108-65-6						*	*	*		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0						*	*	*		
ethylbenzene	100-41-4	*	1000 LBS			*	*	*	*	*	*
carbon black	1333-86-4						*	*	*	*	*
benzene	71-43-2	*	10 LBS			*	*	*	*	*	*
aniline	62-53-3	*	5000 LBS	*	1000 LBS	*	*	*	*	*	*

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

EHS Review/Issue Date: 04/16/2014

File: IACAB_MSDS_ENGUSA_005.pdf

Page 8 of 9

Section 16: Other Information

HMIS Codes Health 2 Flammability 4 Reactivity 0

Key to Abbreviations:

* Item appears on indicated list (or inventory)

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstract Service Registry Number

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CERCLA RQ CERCLA Reportable Quantity
CFR Code of Federal Regulations
CPR Cardiopulmonary resuscitation
DSL Domestic Substances List of Canada

EINECS European Inventory of Existing Chemical Substances
EPCRA Emergency Planning and Community Right-to-know Act

EPCRA EHS EPCRA Extremely Hazardous Substance
EPCRA TPQ EPCRA Threshold Planning Quantity

°F Fahrenheit degrees g/l Grams per liter

gal Gallons

IARC International Agency for Research on Cancer

Ibs or LBS Pounds

MGM3 Milligrams per cubic meter
MIR Maximum Incremental Reactivity
MSDS Material Safety Data Sheet
NCP WHMIS Non-Controlled Product

NIOSH National Institute of Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

PPM Parts per million

Proposition 65 California's Safe Drinking Water and Toxic Enforcement Act

SARA Superfund Amendments and Reauthorization Act

TLV Threshold Limit Value

TSCA Toxic Substances Control Act

USEPA United States Environmental Protection Agency

VOC Volatile Organic Compound

VOL Volume WT Weight

WHMIS Canadian Workplace Hazardous Materials Information System

UN United Nations

EHS Review/Issue Date:04/16/2014

Page 9 of 9