Safety Data Sheet



1. Identification				
Product Information: Product Name:	M267-0364			
	PRO-MARK® HEARTWOOD WALNUT			
Recommended Use:	Surface Preparation or Protection			
Supplied by:	Mohawk Finishing Products Division of RPM Wood Finishes Group, Inc. 2220 US Hwy 70 SE Suite 100 Hickory, NC 28602 USA			
Company Phone No:	(800) 522-8266			
Emergency Phone No. CHEMTREC:	(800) 424-9300			
International Emergency No. CHEMTREC:	(703) 527-3887 (Collect calls are accepted)			

2. Hazards Identification

GHS	Clas	sif	ication	l	
Flam	Liq.	2,	STOT	SE	3 NE

Symbol(s) of Product



Signal Word Danger

Possible Hazards

2% of the mixture consists of ingredients of unknown acute toxicity

H225

GHS HAZARD STATEMENTS Flammable Liquid, category 2

STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
GHS LABEL PRECAUTIONARY STATE	MENTS	
P210	Keep away f smoking.	rom heat, hot surfaces, sparks, open flames and other ignition sources. No
P280	Wear protec	tive gloves/protective clothing/eye protection/face protection.
P405	Store locked	lup.
P303+P361+P353	IF ON SKIN water/showe	(or hair): Take off immediately all contaminated clothing. Rinse skin with r.
P403+P233	Store in a we	ell-ventilated place. Keep container tightly closed.
P312	Call a POIS	ON CENTER or doctor/physician if you feel unwell.
P304+P340	IF INHALED	: Remove person to fresh air and keep comfortable for breathing.
P403+P235	Store in a we	ell-ventilated place. Keep cool.

Highly flammable liquid and vapour.

GHS SDS PRECAUTIONARY STATEMENTS

Product:	M267-0364
----------	-----------

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
ethanol	64-17-5	40-55	GHS02	H225
propylene glycol monomethyl ether	107-98-2	10-25	GHS02-GHS06- GHS07	H226-331-336
ethoxypropanol	1569-02-4	10-25	GHS02-GHS07	H226-332-336
dipropylene glycol monomethyl ether	34590-94-8	2.5-10	No Information	No Information
isopropanol	67-63-0	1.0-2.5	GHS02-GHS07	H225-302-319-336
cobalt compound	70851-34-2	1.0-2.5	No Information	No Information

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

FIRST AID - INGESTION: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

FIREFIGHTING EQUIPMENT: This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

7. Handling and Storage



HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits <u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> <u>OSHA PEL-CEILING</u>					
ethanol	N.D.	1000 ppm	1000 ppm	N.D.	
propylene glycol monomethyl ether	50 ppm	100 ppm	N.D.	N.D.	
ethoxypropanol	50 ppm	200 ppm	N.D.	N.D.	
dipropylene glycol monomethyl ether	100 ppm	150 ppm	100 ppm	N.D.	
isopropanol	200 ppm	400 ppm	400 ppm	N.D.	
cobalt compound	N.D.	N.D.	N.D.	N.D.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

Personal Protection



RESPIRATORY PROTECTION: Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



EYE PROTECTION: Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

N.I. = No Information

9. Physical and Chemical Properties

Appearance:	Colored Liquid	Physical State:	LIQUID
Odor:	Moderately Strong Alcohol	Odor Threshold:	Not determined
Density, g/cm3:	0.913	pH:	Not determined
Freeze Point, °F:	Not determined	Viscosity:	Not determined
Solubility in Water:	Not determined	Partition Coefficient, n-octanol/ water:	Not determined
Decomposition temperature, °F:	Not determined	Explosive Limits, %:	Not determined
Boiling Range, °F:	> 100 °F	Flash Point, °F:	55 ° F
Combustibility:	Supports Combustion	Auto-Ignition Temperature, °F:	Not determined
Evaporation Rate:	Faster than Diethyl Ether	Vapor Pressure, mmHg:	Not determined
Vapor Density:	Not determined		

10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks.

INCOMPATIBILITY: Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

11. Toxicological information

\$*

Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY:

Skin Contact, Inhalation

Acute Toxicity Values The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat

107-98-2	propylene glycol monomethyl ether
1569-02-4	ethoxypropanol
34590-94-8	dipropylene glycol monomethyl ether
67-63-0	isopropanol

5000 mg/kg Rat 4400 mg/kg Rat 5230 mg/kg Rat 1870 mg/kg Rat 13000 mg/kg Rabbit 8100 mg/kg Rabbit 9500 mg/kg Rabbit 4059 mg/kg Rabbit >6 mg/L Rat 15 >20 mg/l 72.6 mg/L Rat

N.I. = No Information

12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

13. Disposal Information



Product

DISPOSAL METHOD: Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: CONSUMER COMMODITY

IATA: ID8000, CONSUMER COMMODITY, 9

IMDG: LIMITED QUANTITY UN1263

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

CALIFORNIA PROPOSITION 65

No listed chemicals.

16. Other Informa	ition					
Revision Date:	7/25/2021		Sup	persedes C	Date:	7/23/2020
Reason for revision:	for revision: Substance and/or Product Properties Changed in Section(s): 09 - Physical & Chemical Information 11 - Toxicological Information			on(s):		
Datasheet produced by	Regulatory De	epartment				
HMIS Ratings:						
Health: 2	Flammability:	3	Reactivity:	0	Personal Protection:	Х
Volatile Organic Comp Text for GHS Hazard	-		740 describing each in	aredient [.]		
H225 H226 H302 H319 H331 H332 H336 Icons for GHS Pictogr	Highly flammable liqu Flammable liquid and Harmful if swallowed. Causes serious eye i Toxic if inhaled. Harmful if inhaled. May cause drowsines rams shown in Section	l vapour. rritation. ss or dizzin	ess.	nt:		
GHS02	*					
GHS06						
GHS07		ur procept	knowledge. It is no	t o opocifi	cation and it does not quarar	atao anasifia

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.