Safety Data Sheet



1. Identification		
Product Information: Product Name:	M520-01436 ULTRA® PENETRATING STAIN RAW UMBER QT	
Recommended Use:	Surface Preparation or Protection	
Supplied by:	Mohawk Finishing Products Division of RPM Wood Finishes Group, Inc. 2220 US Hwy 70 SE Suite 100 Hickory, NC 28602 USA	
Company Phone No:	(800) 522-8266	
Emergency Phone No. CHEMTREC:	(800) 424-9300	
International Emergency No. CHEMTREC:	(703) 527-3887 (Collect calls are accepted)	

2. Hazards Identification

GHS Classification

Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE

Symbol(s) of Product



Signal Word Danger

P240

Possible Hazards

2% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

GING HAZARD STATEWIENTS		
Flammable Liquid, category 2	H225 Highly flammable liquid and vapour.	
STOT, single exposure, category 3, NE	H336 May cause drowsiness or dizziness.	
Eye Irritation, category 2	H319 Causes serious eye irritation.	
GHS LABEL PRECAUTIONARY STATE	MENTS	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
CHS SDS DDECALITIONADY STATEM		

GHS SDS PRECAUTIONARY STATEMENTS

Ground/bond container and receiving equipment.

P241	Use explosion-proof electrical/ventilating/lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
acetone	67-64-1	75-100	GHS02-GHS07	H225-302-319-336
ethanol	64-17-5	2.5-10	GHS02	H225
propylene glycol monoethyl ether	52125-53-8	1.0-2.5	GHS07	H332
propylene glycol monomethyl ether	107-98-2	0.1-1.0	GHS02-GHS06	H226-331-336

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Gently wash with plenty of Soap and Water. If skin irritation occurs: Get medical advice/ attention.

FIRST AID - INGESTION: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

FIREFIGHTING EQUIPMENT: This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

7. Handling and Storage



HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits					
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING	
acetone ethanol propylene glycol monoethyl ether	250 ppm N.D. N.D.	500 ppm 1000 ppm N.D.	1000 ppm 1000 ppm N.D.	N.D. N.D. N.D.	
propylene glycol monomethyl ether	50 ppm	100 ppm	N.D.	N.D.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

Personal Protection



RESPIRATORY PROTECTION: A NIOSH-approved air-purifying respirator with the appropriate cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.



SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



EYE PROTECTION: Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

9. Physical and Chemical Properties

Appearance:	Colored Liquid	Physical State:	LIQUID
Odor:	Strong Solvent	Odor Threshold:	Not determined
Density, g/cm3:	0.826	pH:	Not determined
Freeze Point, °F:	Not determined	Viscosity:	Not determined
Solubility in Water:	Not determined	Partition Coefficient, n-octanol/ water:	Not determined
Decomposition temperature, °F:	Not determined	Explosive Limits, %:	Not determined
Boiling Range, °F:	> 100 °F	Flash Point, °F:	-4 ° F
Combustibility:	Supports Combustion	Auto-Ignition Temperature, °F:	Not determined
Evaporation Rate:	Faster than Diethyl Ether	Vapor Pressure, mmHg:	Not determined
Vapor Density:	Not determined		

N.I. = No Information

10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks.

INCOMPATIBILITY: Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

11. Toxicological information

Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY:

Eye Contact

Acute Toxicity Values The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	<u>Chemical Name</u>
67-64-1	acetone

Oral LD50 1800 mg/kg Rat Dermal LD50 20000 mg/kg Rabbit 50.1 mg/L Rat

Vapor LC50

64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat
52125-53-8	propylene glycol monoethyl ether	N.I.	N.I.	>20 mg/l
107-98-2	propylene glycol monomethyl ether	5000 mg/kg Rat	13000 mg/kg Rabbit	>6 mg/L Rat

N.I. = No Information

12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

13. Disposal Information



Product

DISPOSAL METHOD: Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: CONSUMER COMMODITY

IATA: CONSUMER COMMODITY, ID 8000

IMDG: LIMITED QUANTITY UN1263

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

CALIFORNIA PROPOSITION 65 CARCINOGENS

This product does not contain a chemical known to the State of California to cause cancer.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

This product does not contain a chemical known to the State of California to cause birth defects or other reproductive harm.

16. Othe	r Informati	ion					
Revision Da	ate:	5/20/2017		Su	persedes D	Date:	2/17/2017
Reason for	revision:		Substance Hazardous Flag Changed Substance Hazard Threshold % Changed				
Datasheet	produced by:	Regulatory	Regulatory Department				
HMIS Ratii	ngs:						
Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	Х
<u> </u>		<u> </u>					

800

Volatile Organic Compounds, gr/ltr:

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flat H302 Ha H319 Ca H331 To H332 Ha	ghly flammable liquid and vapour. Immable liquid and vapour. Imful if swallowed. Uses serious eye irritation. xic if inhaled. Imful if inhaled. Ing cause drowsiness or dizziness.
---------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.