

Safety Data Sheet acc. to OSHA HCS

Printing date 08/30/2021

Version number 74

Reviewed on 08/30/2021

1 Identification

- · Product identifier
 - Product number CLT3

```
• Trade name: Kromolux conc. Red

• Application of the substance / the mixture For professional use
```

· Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:* IVM Chemicals srl Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labeling: 1-methoxy-2-propanol 2-methoxypropanol
- · Hazard statements
- H226 Flammable liquid and vapor.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements
- P210Keep away from heat/sparks/open flames/hot surfaces. No smoking.P241Use explosion-proof electrical/ventilating/lighting/equipment.P261Avoid breathing dust/fume/gas/mist/vapors/spray
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P405Store locked up.P501Dispose of contended
 - Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)





Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Printing date 08/30/2021

FIRE

Product number CLT3 Trade name: Kromolux conc. Red

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4) HEALTH 0 Health = 03 REACTIVITY 0

Fire = 3Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangero	us components:	
107-98-2	1-methoxy-2-propanol	50-74.99%
	 ♦ Flam. Liq. 3, H226 ♦ STOT SE 3, H336 	
1589-47-5	2-methoxypropanol	≥0.1-<0.5%
	 Flam. Liq. 3, H226 Repr. 1B, H360 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335 	

4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- personal protective equipment for first aid responders is recommended. (please see section 8)
- · After inhalation: Supply fresh air: consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eve contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
- Alcohol resistant foam
- Alcohol resistant foam, CO, powder, water spray/mist.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

(Contd. on page 3)

US

Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3

Trade name: Kromolux conc. Red

(Contd. of page 2)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Protect against electrostatic charges. Keep respiratory protective device available.

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, s Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation. Reference to other sections See Section 7 for information on safe handling. See Section 13 for disposal information. Protective Action Criteria for Chemicals 	awdust).
· PAC-1:	
107-98-2 1-methoxy-2-propanol	100 ppm
· PAC-2:	
107-98-2 1-methoxy-2-propanol	160 ppm
· PAC-3:	
107-98-2 1-methoxy-2-propanol	660 ppm
 7 Handling and storage Handling: Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols. Protect against electrostatic charges. Keep respiratory protective device available. Use explosion-proof apparatus / fittings and spark-proof tools. Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. 	

(Contd. on page 4)



Printing date 08/30/2021



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3 Trade name: Kromolux conc. Red

(Contd. of page 3)

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

107-98-2 1-methoxy-2-propanol

- REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm
- TLV Short-term value: 100 ppm Long-term value: 50 ppm A4

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Pregnant women should strictly avoid inhalation or skin contact.
 - · Breathing equipment:
 - Short term filter device:



Suitable respiratory protective device recommended.

Filter A

• Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

(Contd. on page 5)



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3 Trade name: Kromolux conc. Red

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and c • General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
• Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
· Change in condition	
 Melting point/Melting range: 	Undetermined.
· Boiling point/Boiling range:	120.3 °C (248.5 °F)
· Flash point:	35 °C (95 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosi air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.3 Vol %
· Upper:	~20 Vol %
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
• Density (+/- 0,03) at 20 °C (68 °F):	0.945 g/cm³ (7.886 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not determined.
· Partition coefficient (n-octanol/water): Not determined.
	(Contd. on pag



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3 Trade name: Kromolux conc. Red

		(Contd. of page
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20 •C (68 •F):</i>	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	88.60 %	
	837.3 g/l / 6.99 lb/gal	
· Solids content:	11.4 %	
· Other information (HAPS)		
None of the ingredients is listed.		
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended • **Thermal decomposition** / **conditions to be avoided:**
 - No decomposition if used according to specifications.
- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects May damage fertility or the unborn child.
 - Acute toxicity:

· LD/LC50 values that are relevant for classification:

107-98-2 1-methoxy-2-propanol			
Oral	LD50	4,016 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (rabbit)	
Inhalativ	re LC50/4 h	4,016 mg/kg (mouse) 5,001 mg/kg (rabbit) 5,001 mg/l (mouse)	

• Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Causes serious eye irritation.

Sensitization: No sensitizing effects known.

· Additional toxicological information:

May cause drowsiness or dizziness. May cause drowsiness or dizziness.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

US



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3

Printing date 08/30/2021

Trade name: Kromolux conc. Red

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

107-98-2 1-methoxy-2-propanol

EC50 21,100 mg/l (daphnia) (48 h)

LC50 (96h) 6,812 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable

107-98-2 1-methoxy-2-propanol.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN1263
· Note	Check the viscosity at section 9
· UN proper shipping name	
· DOT	Paint
· IMDG, IATA	PAINT



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3 Trade name: Kromolux conc. Red

Printing date 08/30/2021

	(Contd. of page
Transport hazard class(es)	
·DOT	
П.М. П. С.	
· Class	3 Flammable liquids
· Label	3
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
Packing group	
· DOT, IMDG, IATA	<i>III</i>
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user W	arning: Flammable liquids
· Hazard identification number (Kemler code)): 30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
Transport in bulk according to Annex II of	
	ot applicable.
Transport/Additional information:	
·IMDG	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 3 ml
	Maximum net quantity per outer packaging
	1000 ml
	N 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

⁻ US



Safety Data Sheet acc. to OSHA HCS

Printing date 08/30/2021

Version number 74

Reviewed on 08/30/2021

Product number CLT3

Trade name:	Kromolux conc. Red

	(Contd. of page 8
• Section 313 (Specific toxic chemical listings) :	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
1589-47-5 2-methoxypropanol	≥0.1-<0.5%
• Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	

• TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 08/30/2021 / 73 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3



Safety Data Sheet acc. to OSHA HCS

Version number 74

Reviewed on 08/30/2021

Product number CLT3 Trade name: Kromolux conc. Red

(Contd. of page 9)

US

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer

• * Data compared to the previous version altered.