

Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2020

Version number 334

Reviewed on 03/25/2020

1 Identification

- · Product identifier
 - · Product number KMT20
 - Trade name: <u>KROMOPAST LEMON YELLOW</u> • Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - Manufacturer/Supplier: IVM Chemicals srl Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
 - · Emergency telephone number:
 - ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.Eye Irrit. 2A H319 Causes serious eye irritation.STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

 Hazard-determining components of labeling: n-butyl acetate xylene ethylbenzene 2-methoxy-1-methylethyl acetate

(Contd. on page 2)

US



Reviewed on 03/25/2020

Printing date 03/25/2020

Version number 334

Product number KMT20	
Trade name: KROMOPAST	- LEMON YELLOW

	(Contd. of page 1)
\cdot Hazard statements	l de la constante de
H226 Flammable	liquid and vapor.
H315 Causes ski	n irritation.
H319 Causes se	rious eye irritation.
H350 May cause	cancer.
H336 May cause	drowsiness or dizziness.
H373 May cause	e damage to the hearing organs through prolonged or repeated exposure.
	xposure: Oral, Inhalation.
· Precautionary stat	tements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P35	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse
	skin with water/shower.
P305+P351+P33	88 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Classification system	-
· NFPA ratings (scale (
3 Health Fire =	=2
· HMIS-ratings (scale)	0 - 4)
HEALTH*2HealthFIRE3Fire =	

3 Composition/information on ingredients

Reactivity = 0

· Chemical characterization: Mixtures

REACTIVITY 0

· Description: Mixture: consisting of the following components.

123-86-4	n-butyl acetate	20-24.99%	
	 Flam. Liq. 3, H226 STOT SE 3, H336 		
108-65-6	2-methoxy-1-methylethyl acetate	10-12.49%	
	 Flam. Liq. 3, H226 STOT SE 3, H336 		
1330-20-7	xylene	10-12.49%	
	 Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412 		
100-41-4	ethylbenzene	2.5-4.99%	
	 Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412 	-1	

(Contd. of page 2)

≥0.1-<0.5%

ivm Chemicals

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/25/2020

Printing date 03/25/2020

Version number 334

Product number KMT20

Trade name: KROMOPAST - LEMON YELLOW

64-17-5 ethanol

ethanol Flam. Liq. 2, H225

Carc. 1A, H350 Eve Irrit. 2A, H319

4 First-aid measures

\cdot Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

• After swallowing: Do not induce vomiting; immediately call for medical help.

- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11. No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



Printing date 03/25/2020

Version number 334

Reviewed on 03/25/2020

Product number KMT20 Trade name: KROMOPAST - LEMON YELLOW

Ensure ade	equate ventilation	(Contd. of page 3)
	from ignition sources	
	ental precautions: Do not allow to enter sewers/ surface or ground water. and material for containment and cleaning up:	
	h liquid-binding material (sand, diatomite, acid binders, universal binders, s	awdust).
Dispose co	ontaminated material as waste according to Section 13.	,
	equate ventilation.	
	e to other sections on 7 for information on safe handling.	
	n 8 for information on personal protection equipment.	
See Sectio	n 13 for disposal information.	
	Action Criteria for Chemicals	
· PAC-1:		
	n-butyl acetate	5 ppm
	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7		130 ppm
100-41-4	ethylbenzene	33 ppm
64-17-5	ethanol	1,800 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
64-17-5	ethanol	3300* ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
64-17-5	ethanol	15000* ppm

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
 Use explosion-proof apparatus / fittings and spark-proof tools.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

(Contd. on page 5)

US



Printing date 03/25/2020

Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

roduct	unah ar	KMT20		
roduct n rade nar		-	LEMON YELLOW	
				(Contd. of page
		or safe storage,	including any incompatibilities	
	rage: Roquiro	monts to be met h	storerooms and receptacles:	
	-	e solvent resistant	-	
			autions, the expiration date for t	he use, if not indicated, is f
		/ date of goods.	no reported expiration date , it mea	one that the product must be u
		3 months.		
			in one common storage facility: Not	
			t storage conditions: Keep receptacl bical of the product and the instruct	
Speci	nc enu			
8 Expo	osure e	controls/pers	onal protection	
· Addit	ional in	formation abou	t design of technical systems: No	o further data; see item 7.
	ol para		-	
	· ·		that require monitoring at the work	place:
	-	utyl acetate (20-2		
PEL		term value: 710 n	,	
REL	-	-term value: 950 r	•	
	Long-	term value: 710 n	ng/m³, 150 ppm	
TLV		term value: 712 r		
400.0	-	term value: 238 n		
			ethyl acetate (10-12.49%)	
	-	term value: 50 pp lene (10-12.49%)		
PEL		term value: 435 n		
REL	-	term value: 435 n	•	
NLL		term value: 435 n		
TLV	-	-term value: 651 r		
		term value: 434 n		
100-4	1-4 ethy	vlbenzene (2.5-4	.99%)	
PEL	Long-	term value: 435 n	ng/m³, 100 ppm	
REL		-term value: 545 r		
	-	term value: 435 n		
TLV	Long-i BEI	term value: 87 mg	g/m³, 20 ppm	
64-17		nol (≥0.1-<0.5%)		
PEL	Long-	term value: 1900	mg/m³, 1000 ppm	
REL	Long-	term value: 1900	mg/m³, 1000 ppm	
TLV	Short-	term value: 1880	mg/m³, 1000 ppm	
	· Ingr	edients with biolog	rical limit values:	
1330-2	20-7 xy	lene (10-12.49%)		
		reatinine		
٨	/ledium:			
-		nd of shift er: Methylhippurio	acids	
	ramet			
	Paramet			(Contd. on page




Printing date 03/25/2020

Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020



(Contd. on page 7)

115

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

Product number KMT20 Trade name: KROMOPAST - LEMON YELLOW

Printing date 03/25/2020

Information on basic physical and o	chemical properties	
· General Information		
· Appearance:		
· Form:	Fluid	
· Color:	According to product specification	
• Odor:	Characteristic	
• Odor threshold:	Not determined.	
• <i>pH-value at 20</i> • <i>C</i> (68 • <i>F</i>):	6	
· Change in condition		
• Melting point/Melting range:	Undetermined.	
• Boiling point/Boiling range:	124-128 °C (255.2-198.4 °F)	
· Flash point:	25 °C (77 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	430 °C (806 °F)	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, forma	tion of explosi
-	air/vapor mixtures are possible.	
· Explosion limits:		
Lower:	1 Vol %	
· Upper:	10.8 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.045 g/cm³ (8.721 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20 •C (68 •F):</i>	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	0.0 %	
· VOC content:	49.09 %	
	513.0 g/l / 4.28 lb/gal	
· Solids content:	50.9 %	
Other information (HAPS)		
1330-20-7 xylene		10-12.49
100-41-4 ethylbenzene		2.5-4.99%
Other information /	No further relevant information available.	

(Contd. on page 8)



Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

Product number KMT20

Printing date 03/25/2020

Trade name: KROMOPAST - LEMON YELLOW

(Contd. of page 7)

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

• Chemical stability The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- Possibility of hazardous reactions

Reacts with oxidizing agents.

Vapours may form explosive mixtures with air

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

Causes serious eye irritation.

· Acute toxicity:

· Acute to	· Acute toxicity:				
· LD/.	· LD/LC50 values that are relevant for classification:				
123-86-4	n-butyl ac	etate			
Oral	LD50	10,760 mg/kg (mouse)			
Dermal	LD50	14,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	21.1 mg/l (mouse)			
108-65-62	2-methoxy	/-1-methylethyl acetate			
Oral	LD50	8,532 mg/kg (mouse)			
Dermal	LD50	5,001 mg/kg (rabbit)			
Inhalative	LC50/4 h	35.7 mg/l (mouse)			
1330-20-7	' xylene				
Oral	LD50.	3,523 mg/kg (mouse)			
Dermal	LD50.	12,126 mg/kg (rabbit)			
Inhalative	LC50/4h.	27.571 mg/l (mouse)			
100-41-4	ethylbenz	ene			
Oral	LD50	3,500 mg/kg (mouse)			
Dermal	LD50	15,486 mg/kg (rabbit)			
Inhalative	LC50/4 h	17.2 mg/l (mouse)			
64741-65-	7 Naphtha	a (petroleum), heavy alkylate			
Oral	LD50	6,001 mg/kg (mouse)			
Dermal	LD50	3,001 mg/kg (rabbit)			
64-17-5 et	thanol				
Oral	LD50	10,470 mg/kg (mouse)			
Dermal	LD50	20,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	124.7 mg/l (mouse)			
	· Primary irritant effect:				
	on the skin: Irritant to skin and mucous membranes.				
	• on the eye: Irritating effect. • Sensitization: No sensitizing effects known.				
		ogical information:			
Irritant					
Causes	s skin irrita				
O a · · a a		invitation			



Printing date 03/25/2020

Chemicals

coatings & polymers technologies

iV

Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

		(O
May cau	use drowsiness or dizziness.	(Contd. of page
May cau	use damage to the hearing organs through prolonged or repeated exposite contact of the second se	sure. Route
	s Fatty acids, tallow, oleylamine compounds. May produce an allergic reac	tion.
	inogenic categories	
	lbenzene n IARC MONOGRAPHS VOLUME 77/2000	
	an carcinogenicity data	
styre	studies of workers potentially exposed to ethylbenzene in a productio one polymerization plant were available. In the first study, no excess of car found but the description of methods was insufficient to allow proper eva	ncer inciden
	ng. In the second study, no cancer mortality excess was observed during 5 years.	the follow-
of 15	years.	the follow-
of 15 Evalu	years. uation	
of 15 Evalu There	years.	zene.There
of 15 Evalı Ther suffic	years. uation e is inadequate evidence in humans for the carcinogenicity of ethylben	zene.There
of 15 Evalu There suffic · IA	years. uation ie is inadequate evidence in humans for the carcinogenicity of ethylben. cient evidence in experimental animals for the carcinogenicity ofethylbenze	zene.There
of 15 Evalu There suffic · IA	years. Wation The is inadequate evidence in humans for the carcinogenicity of ethylben Chent evidence in experimental animals for the carcinogenicity of ethylbenze WARC (International Agency for Research on Cancer - Cl. 1 and 2) Ethylbenzene	zene. There ne.
of 15 Evalu Ther suffic · IA 100-41-4 e 64-17-5 e	years. Wation The is inadequate evidence in humans for the carcinogenicity of ethylben Chent evidence in experimental animals for the carcinogenicity of ethylbenze WARC (International Agency for Research on Cancer - Cl. 1 and 2) Ethylbenzene	zene.There ne. 2
of 15 Evalu There suffic · IA 100-41-4 e 64-17-5 e	years. Uation The is inadequate evidence in humans for the carcinogenicity of ethylben Scient evidence in experimental animals for the carcinogenicity of ethylbenze ARC (International Agency for Research on Cancer - Cl. 1 and 2) Southylbenzene Southanol	zene.There ne. 2
of 15 Evalu Ther suffic · IA 100-41-4 e 64-17-5 e · N None of the	years. Wation The is inadequate evidence in humans for the carcinogenicity of ethylben Crient evidence in experimental animals for the carcinogenicity of ethylbenze ARC (International Agency for Research on Cancer - Cl. 1 and 2) Pathylbenzene Pathanol TP (National Toxicology Program)	zene.There ne. 2
of 15 Evalu There suffic · IA 100-41-4 e 64-17-5 e · N None of the	years. Wation The is inadequate evidence in humans for the carcinogenicity of ethylben Scient evidence in experimental animals for the carcinogenicity of ethylbenze MRC (International Agency for Research on Cancer - Cl. 1 and 2) Southylbenzene Southanol TP (National Toxicology Program) To ingredients is listed.	zene.There ne. 2

• Aquatic to	•	
123-86-4 n-	butyl acetate	
EC50	397 mg/l (algae) (72 h)	
	44 mg/l (daphnia) (48 h)	
LC50 (96h)	18 mg/l (Fish)	
108-65-6 2-	methoxy-1-methylethyl acetate	
EC50	1,001 mg/l (algae) (72 h)	
	501 mg/l (daphnia) (48 h)	
LC50 (96h)	134 mg/l (Fish)	
1330-20-7 x	<i>cylene</i>	
EC50	2.2 mg/l (algae) (72h)	
LC50 48h	1 mg/l (daphnia)	
LC50 (96h)	2.6 mg/l (Fish)	
100-41-4 et	hylbenzene	
EC50	438 mg/l (algae) (72h)	
	1.8 mg/l (daphnia) (48 h)	
LC50 (96h)	12.1 mg/l (Fish)	
64-17-5 eth	anol	
EC50	5,012 mg/l (daphnia) (48 h)	_
	(Contd. on page	ə 1(

iVM Chemicals

Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

Product number KMT20

Printing date 03/25/2020

Trade name: KROMOPAST - LEMON YELLOW

(Contd. of page 9)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:


Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.





Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2020

Version number 334

Reviewed on 03/25/2020

Product number KMT20

Trade name: KROMOPAST - LEMON YELLOW

		(Contd. of page 1
· Label	3	
Packing group		
· DOT, IATA	<i>III</i>	
·IMDG	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	ll of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
· Remarks:	> 450 l: 3 F1, III	
· IMDG		
· Remarks:	> 30 I: 3, III	
UN "Model Regulation":	Not applicable	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

Si iii i		
· Secti	on 355 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Secti	on 313 (Specific toxic chemical listings) :	
1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%
67-63-0	propan-2-ol	<0.01%
· TSCA (7	Foxic Substances Control Act):	
All compor	ents have the value ACTIVE.	
· Haza	rdous Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Proposit	ion 65	
· Cher	nicals known to cause cancer:	
100-41-4	ethylbenzene	* 2.5-4.99%
· Cher	nicals known to cause reproductive toxicity for females:	
70657-70-4	2-methoxypropyl acetate	<0.1%
· Cher	nicals known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Cher	nicals known to cause developmental toxicity:	
64-17-5 et	hanol	≥0.1-<0.5%
		(Contd. on page 12)
		US



Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2020

Version number 334

Reviewed on 03/25/2020

Product number KMT20

Trade name: KROMOPAST - LEMON YELLOW

			(Contd. of page 11)		
· Carcino	genic categories				
· EPA	(Environmental Protection Agency)				
1330-20-7	xylene	Ι	10-12.49	9%	
100-41-4	ethylbenzene	D	2.5-4.99	%	
78-93-3	butanone	Ι	<0.01%	6	
· TLV	(Threshold Limit Value established by ACGIH)				
1330-20-7	xylene		A	44	
100-41-4	ethylbenzene		F	43	
64-17-5	ethanol		F	43	
67-63-0	propan-2-ol		A	44	
· NIOS	SH-Ca (National Institute for Occupational Safety and Health)				
None of the	e ingredients is listed.				

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 03/25/2020 / 333

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Carc. 1A: Carcinogenicity - Category 1A Carc. 2: Carcinogenicity - Category 2

(Contd. on page 13)

coatings & polymers technologies

Printing date 03/25/2020

Safety Data Sheet acc. to OSHA HCS

Version number 334

Reviewed on 03/25/2020

Product number KMT20 Trade name: KROMOPAST - LEMON YELLOW

(Contd. of page 12) STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 **Sources** REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site INRS Fiche Toxicologique

IARC International agency for research on cancer * Data compared to the previous version altered.

US