

## 1 Identification

- **Product identifier**

- *Product number* KMT80
- *Trade name:* **KROMOPAST BLEU**
- *Application of the substance / the mixture* For professional use

- **Details of the supplier of the safety data sheet**

- *Manufacturer/Supplier:*  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
- *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

- Flam. Liq. 2 H225 Highly flammable liquid and vapor.*  
*Skin Irrit. 2 H315 Causes skin irritation.*  
*Eye Irrit. 2A H319 Causes serious eye irritation.*  
*Carc. 2 H351 Suspected of causing cancer.*  
*STOT SE 3 H336 May cause drowsiness or dizziness.*  
*STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.*  
*Route of exposure: Oral, Inhalation.*

- **Label elements**

- *GHS label elements*  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* **Danger**
- *Hazard-determining components of labeling:*  
xylene  
n-butyl acetate  
ethylbenzene  
4-methylpentan-2-one
- *Hazard statements*  
*H225 Highly flammable liquid and vapor.*  
*H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H351 Suspected of causing cancer.*  
*H336 May cause drowsiness or dizziness.*  
*H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.*

(Contd. on page 2)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 1)

**Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



**HMIS-ratings (scale 0 - 4)**



**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

**Description:** Mixture: consisting of the following components.

**Dangerous components:**

123-86-4	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	15-19.99%
1330-20-7	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	10-12.49%
108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-9.99%
100-41-4	ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	2.5-4.99%
108-10-1	4-methylpentan-2-one Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-4.99%

US

(Contd. on page 3)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 2)

#### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Do not induce vomiting; immediately call for medical help.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

- **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

- **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

- **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)

**Product number KMT80****Trade name: KROMOPAST BLEU**

(Contd. of page 3)

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
108-10-1	4-methylpentan-2-one	75 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
108-10-1	4-methylpentan-2-one	500 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
108-10-1	4-methylpentan-2-one	3000* ppm

## 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 5)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
  - **Storage:**
    - **Requirements to be met by storerooms and receptacles:**  
 Store in a cool, well-ventilated area, away from heat and sources of ignition  
 Provide solvent resistant, sealed floor.  
 Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.  
 In cases where there is no reported expiration date, it means that the product must be used within 8 months.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.
  - **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

### 108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 6)

**Product number KMT80**  
**Trade name: KROMOPAST BLEU**

(Contd. of page 5)

REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

**108-10-1 4-methylpentan-2-one**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
 The glove material has to be impermeable and resistant to the product .

(Contd. on page 7)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 6)

- **Material of gloves**  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

- **Form:** Fluid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

#### · Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 117 °C (242.6 °F)

· **Flash point:** 14 °C (57.2 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 430 °C (806 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

#### · Explosion limits:

- **Lower:** 1 Vol %
- **Upper:** 10.8 Vol %

· **Vapor pressure at 20 °C (68 °F):** 20.2 hPa (15.2 mm Hg)

· **Density (+/- 0,03) at 20 °C (68 °F):** 1.052 g/cm<sup>3</sup> (8.779 lbs/gal)

- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

(Contd. on page 8)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 7)

· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>		Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b> Not determined.		
· <b>Viscosity:</b>		
· <b>Dynamic:</b>		Not determined.
· <b>Kinematic at 20 °C (68 °F):</b>		55 s (ISO 6 mm)
· <b>Oxidising properties:</b>		N.A.
· <b>Solvent content:</b>		
· <b>VOC content:</b>		39.92 % 420.0 g/l / 3.50 lb/gal
· <b>Solids content:</b>		60.1 %
· <b>Other information (HAPS)</b>		
1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%
108-10-1	4-methylpentan-2-one	2.5-4.99%
· <b>Other information</b>		No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimate)</b>		
Dermal	LD50	9,426 mg/kg (rabbit)
Inhalative	LC50/4 h	70.6 mg/l (mouse)
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10,760 mg/kg (mouse)

(Contd. on page 9)

us



**Product number KMT80**  
**Trade name: KROMOPAST BLEU**

(Contd. of page 8)

Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
<b>1330-20-7 xylene</b>		
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
<b>108-10-1 4-methylpentan-2-one</b>		
Oral	LD50	2,080 mg/kg (mouse)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	16.6 mg/l (mouse)
<b>64741-65-7 Naphtha (petroleum), heavy alkylate</b>		
Oral	LD50	6,001 mg/kg (mouse)
Dermal	LD50	3,001 mg/kg (rabbit)

- **Primary irritant effect:**

- *on the skin:* Irritant to skin and mucous membranes.

- *on the eye:* Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

- **Carcinogenic categories**

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

**Evaluation**

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

(Contd. on page 10)

**Product number KMT80**  
**Trade name: KROMOPAST BLEU**

(Contd. of page 9)

· <b>IARC (International Agency for Research on Cancer - Cl. 1 and 2)</b>		
100-41-4	ethylbenzene	2B
108-10-1	4-methylpentan-2-one	2B
· <b>NTP (National Toxicology Program)</b>		
None of the ingredients is listed.		
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

## 12 Ecological information

### · Toxicity

· <b>Aquatic toxicity:</b>	
<b>123-86-4 n-butyl acetate</b>	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
<b>1330-20-7 xylene</b>	
EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
<b>100-41-4 ethylbenzene</b>	
EC50	438 mg/l (algae) (72h) 1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
<b>108-10-1 4-methylpentan-2-one</b>	
EC50	201 mg/l (daphnia) (48 h)
LC50 (96h)	180 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· <b>Substances Easily biodegradable</b>		
123-86-4	n-butyl acetate	.
1330-20-7	xylene	.
108-65-6	2-methoxy-1-methylethyl acetate	.
100-41-4	ethylbenzene	.
108-10-1	4-methylpentan-2-one	.

### · Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 11)

**Product number** KMT80  
**Trade name:** KROMOPAST BLEU

(Contd. of page 10)

- **Additional ecological information:**
  - **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
  - **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation:**


Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Hand over to hazardous waste disposers.  
Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
  - **DOT, IMDG, IATA** UN1263
  - **Note** Check viscosity and flash point at section 9

- **UN proper shipping name**
  - **DOT** Paint
  - **IMDG, IATA** PAINT

- **Transport hazard class(es)**
  - **DOT**



    - **Class** 3 Flammable liquids
    - **Label** 3
    - **Class** 3 Flammable liquids
    - **Label** 3

- **IMDG, IATA**



  - **Class** 3 Flammable liquids
  - **Label** 3

(Contd. on page 12)

**Product number KMT80**  
**Trade name: KROMOPAST BLEU**

(Contd. of page 11)

· <b>Packing group</b> · DOT, IMDG, IATA	III
· <b>Environmental hazards:</b> · Marine pollutant:	No
· <b>Special precautions for user</b> · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids - F-E, S-E A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b> · DOT · Remarks:	> 450 I: 3 F1, II
· <b>IMDG</b> · Limited quantities (LQ) · Excepted quantities (EQ)  · Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml > 450 I: 3, II
· <b>IATA</b> · Remarks:	> 30 I: 3, II
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
Requirements of Federal Register

· Various regulations  
· SARA

· <b>Section 355 (extremely hazardous substances):</b>
None of the ingredients is listed.

· <b>Section 313 (Specific toxic chemical listings) :</b>	
1330-20-7 xylene	10-12.49%
100-41-4 ethylbenzene	2.5-4.99%
108-10-1 4-methylpentan-2-one	2.5-4.99%

· <b>TSCA (Toxic Substances Control Act):</b>
All components have the value ACTIVE.

· <b>Hazardous Air Pollutants</b>
1330-20-7 xylene
100-41-4 ethylbenzene

(Contd. on page 13)

**Product number KMT80**  
**Trade name: KROMOPAST BLEU**

(Contd. of page 12)

108-10-1	4-methylpentan-2-one		
<b>· Proposition 65</b>			
<b>· Chemicals known to cause cancer:</b>			
100-41-4	ethylbenzene	*	2.5-4.99%
108-10-1	4-methylpentan-2-one	*	2.5-4.99%
<b>· Chemicals known to cause reproductive toxicity for females:</b>			
70657-70-4	2-methoxypropyl acetate		<0.1%
<b>· Chemicals known to cause reproductive toxicity for males:</b>			
None of the ingredients is listed.			
<b>· Chemicals known to cause developmental toxicity:</b>			
108-10-1	4-methylpentan-2-one		2.5-4.99%
<b>· Carcinogenic categories</b>			
<b>· EPA (Environmental Protection Agency)</b>			
1330-20-7	xylene	I	10-12.49%
100-41-4	ethylbenzene	D	2.5-4.99%
108-10-1	4-methylpentan-2-one	I	2.5-4.99%
<b>· TLV (Threshold Limit Value)</b>			
1330-20-7	xylene		A4
100-41-4	ethylbenzene		A3
<b>· NIOSH-Ca (National Institute for Occupational Safety and Health)</b>			
None of the ingredients is listed.			

**· National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** IVM Chemicals Srl

**· Contact:** See emergency phone

**· Date of preparation / last revision** 12/09/2021 / 110

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 14)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 12/09/2021

Version number 111

Reviewed on 12/09/2021

**Product number KMT80****Trade name: KROMOPAST BLEU**

(Contd. of page 13)

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL  
and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· \* **Data compared to the previous version altered.**