# **SAFETY DATA SHEET**

W38071

# Section 1. Identification

Product name	: ARROYO 2K Waterborne Polyurethane Topcoat White Flat
Product code	: W38071
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related material	
Manufacturer	: M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone	: (800) 424-9300

number of the company	
Product Information Telephone Number	: (800) 364-1359
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

## Section 2. Hazards identification

White Flat

OSHA/HCS status Classification of the	(29 CFR 1910.1200). : CARCINOGENICITY - Category 2					
substance or mixture	TOXIC TO REPRODUCTION - Category 2					
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1.7% (oral), 1.7% (dermal), 1.7% (inhalation)					
GHS label elements						
Hazard pictograms						
Signal word	: Warning					
Hazard statements	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.					
Precautionary statements						
General	<ul> <li>Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.</li> </ul>					
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.					
Response	: IF exposed or concerned: Get medical advice or attention.					
Date of issue/Date of revision	: 2/8/2022 Date of previous issue : 11/12/2021 Version : 2.01 1/1					
W38071 ARROYO 2K W	aterborne Polyurethane Topcoat SHW-85-NA-GHS-US					

# Section 2. Hazards identification

Storage	: Store locked up.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
Fumed Amorphous Silica	≤3	112945-52-5
2-Methoxymethylethoxypropanol	≤3	34590-94-8
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	≤0.3	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necessary first	t aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date	of revision	: 2/8/2022	Date of previous issue	: 11/12/2021	Version	: 2.01	2/13
W38071	ARROYO 2K Waterborn White Flat	ne Polyurethane	∋ Topcoat		SHW-85-	NA-GHS-US	

# Section 4. First aid measures

#### Most important symptoms/effects, acute and delayed

most important symptoms/e	nects, acute and delayed
Potential acute health effec	<u>ts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>toms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date	of revision	: 2/8/2022	Date of previous issue	: 11/12/2021	Version	: 2.01	3/13
W38071	ARROYO 2K Waterbor White Flat	ne Polyurethane	e Topcoat		SHW-85-	NA-GHS-US	

# Section 6. Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	tainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date	of revision	: 2/8/2022	Date of previous issue
W38071	ARROYO 2K Waterborn White Flat	ne Polyurethane	e Topcoat

:11/12/2021

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	ACGIH TLV (United States, 1/2021). TWA: 10 mg/m <sup>3</sup> 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Fumed Amorphous Silica	112945-52-5	NIOSH REL (United States, 10/2020). TWA: 6 mg/m <sup>3</sup> 10 hours.
2-Methoxymethylethoxypropanol	34590-94-8	ACGIH TLV (United States, 1/2021). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 606 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 909 mg/m <sup>3</sup> 15 minutes. NIOSH REL (United States, 10/2020). Absorbed through skin. TWA: 100 ppm 10 hours. TWA: 600 mg/m <sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 900 mg/m <sup>3</sup> 15 minutes. STEL: 900 mg/m <sup>3</sup> 15 minutes. OSHA PEL (United States, 5/2018). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 600 mg/m <sup>3</sup> 8 hours.
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	77-99-6	None.

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits		
Titanium dioxide	13463-67-7	<ul> <li>CA British Columbia Provincial (Canada, 1/2021).</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> <li>CA Quebec Provincial (Canada, 7/2019).</li> <li>TWAEV: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust.</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 20 mg/m<sup>3</sup> 15 minutes.</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours.</li> </ul>		
Dipropylene glycol monomethyl ether	34590-94-8	CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 909 mg/m <sup>3</sup> 15 minutes. 8 hrs OEL: 606 mg/m <sup>3</sup> 8 hours. 15 min OEL: 150 ppm 15 minutes. CA British Columbia Provincial (Canada, 1/2021). Absorbed through skin. TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019).		
Date of issue/Date of revision : 2/8/2022 Date	e of previous issue	: 11/12/2021 Version : 2.01 5/13		
V38071 ARROYO 2K Waterborne Polyurethane Top White Flat	coat	SHW-85-NA-GHS-US		

# Section 8. Exposure controls/personal protection

Absorbed through skin.TWAEV: 100 ppm 8 hours.TWAEV: 606 mg/m³ 8 hours.STEV: 150 ppm 15 minutes.STEV: 909 mg/m³ 15 minutes.CA Ontario Provincial (Canada, 6/2019).Absorbed through skin.STEL: 150 ppm 15 minutes.TWA: 100 ppm 8 hours.CA Saskatchewan Provincial (Canada,7/2013). Absorbed through skin.STEL: 150 ppm 15 minutes.TWA: 100 ppm 8 hours.CA Saskatchewan Provincial (Canada,T/2013). Absorbed through skin.STEL: 150 ppm 15 minutes.TWA: 100 ppm 8 hours.

#### Occupational exposure limits (Mexico)

	CAS #	Exposure limits
2-Methoxymethylethoxypropanol	34590-94-8	NOM-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.

Appropriate engineering controls Environmental exposure controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be processed on the process equipment and the process equipment				
	will be necessary to reduce emissions to acceptable levels.				
Individual protection measur					
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	,			
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.				
Skin protection					
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	S			
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	g			
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	а			
Date of issue/Date of revision	: 2/8/2022 Date of previous issue : 11/12/2021 Version : 2.01 6/	/13			

Date of issue/Date	of revision	: 2/8/2022	Date of previous issue	: 11/12/2021	Version : 2.01	6/13
W38071	ARROYO 2K Waterb White Flat	oorne Polyuretha	ine Topcoat		SHW-85-NA-GHS-US	

### Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Not available.
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	8.5
Melting point/freezing point	:	Not available.
Boiling point, initial boiling point, and boiling range	:	100°C (212°F)
Flash point	:	Closed cup: Not applicable.
Evaporation rate	:	0.8 (butyl acetate = 1)
Flammability	:	Not available.
Lower and upper explosion limit/flammability limit	:	Lower: 0.6% Upper: 20.4%
Vapor pressure	:	2.3 kPa (17.5 mm Hg)
Relative vapor density	:	1 [Air = 1]
Relative density	:	1.25
Solubility	:	Not available.
Partition coefficient: n- octanol/water	1	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	:	Not applicable.
Aerosol product		
Heat of combustion	1	2.347 kJ/g

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.

Date of issue/Date	e of revision	: 2/8/2022	Date of previous issue	: 11/12/2021	Version	: 2.01	7/13
W38071	ARROYO 2K Waterb White Flat	oorne Polyuretha	ne Topcoat		SHW-85-	NA-GHS-US	

# Section 10. Stability and reactivity

# Hazardous decomposition products

 Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Fumed Amorphous Silica 2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	LD50 Oral LD50 Oral		3160 mg/kg 14000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
2-Methoxymethylethoxypropanol	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Fumed Amorphous Silica	-	2B 3	-

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

### Information on the likely : Not available.

### routes of exposure

#### Potential acute health effects

- Eye contact Inhalation
- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.

Date of issue/Date	of revision	: 2/8/2022	Date of previous issue	: 11/12/2021	Version	: 2.01	8/13
W38071	ARROYO 2K Waterborn White Flat	e Polyurethane	Topcoat		SHW-85-N	NA-GHS-US	

# Section 11. Toxicological information

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health en Not available.	f <u>ects</u>
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Suspected of damaging the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

Numerical measures of toxicity Acute toxicity estimates Not available.

: 11/12/2021

of

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide 2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	10	Fish - Fundulus heteroclitus Daphnia - Daphnia magna	96 hours 48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	-	<1	low

#### Mobility in soil

Soil/water partition : Not available. coefficient (K<sub>oc</sub>)

#### **Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
ate of issue/Date of rev /38071 ARR	v <b>ision</b> : 2/8/20. DYO 2K Waterborne Polyu		issue : 11/12/20		<mark>sion</mark> : 2.01 10/ W-85-NA-GHS-US

Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
pecial precautions	s for user :	consider container mode of transport suitably for that mo prior to shipment, a responsibility of the unloading dangero	sizes. The presence (sea, air, etc.), does r ide of transport. All p and compliance with person offering the us goods must be tra	of a shipping descript not indicate that the prackaging must be re- the applicable regular product for transport	product is packaged viewed for suitability tions is the sole . People loading and as deriving from the

# Section 15. Regulatory information

**TSCA 5(a)2 proposed significant new use rules**: Nonylphenoxypoly(ethoxy)ethanol; 1-Methyl-2-Pyrrolidone

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



Date of issue/Date	of revision	: 2/8/2022	Date of previous issue	: 11/12/2021
W38071	ARROYO 2K Waterbor White Flat	ne Polyurethane	e Topcoat	

# Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

	Classification	Justification				
	CARCINOGENICITY - Category 2 OXIC TO REPRODUCTION - Category 2					
<u>History</u>	listory					
Date of printing	: 2/8/2022					
Date of issue/Date of revision	: 2/8/2022					
Date of previous issue	: 11/12/2021					
Version	: 2.01					
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification at IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffi MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	cient of Pollution From Ships, 1973				

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer. or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

:11/12/2021