



PART NUMBER	SLIDE LENGTH (MM)	SLIDE TRAVEL	* A *	* B *	* C *
301-2590-12	12.00	12.85	4.00	6.40	15.40
301-2590-13	13.00	13.85	4.00	7.20	17.00
301-2590-14	14.00	14.85	4.00	8.00	18.60
301-2590-15	15.00	15.85	4.00	8.80	20.20
301-2590-16	16.00	16.85	4.00	9.60	21.80
301-2590-17	17.00	17.85	4.00	10.40	23.40
301-2590-18	18.00	18.85	4.00	11.20	25.00
301-2590-19	19.00	19.85	4.00	12.00	26.60
301-2590-20	20.00	20.85	4.00	12.80	28.20
301-2590-21	21.00	21.85	4.00	13.60	29.80
301-2590-22	22.00	22.85	4.00	14.40	31.40
301-2590-23	23.00	23.85	4.00	15.20	33.00
301-2590-24	24.00	24.85	4.00	16.00	34.60
301-2590-25	25.00	25.85	4.00	16.80	36.20
301-2590-26	26.00	26.85	4.00	17.60	37.80
301-2590-27	27.00	27.85	4.00	18.40	39.40
301-2590-28	28.00	28.85	4.00	19.20	41.00

- 9. SLIDE IS PROVIDED WITH A DETENT IN THE CLOSED POSITION.
 - 8. SLIDE IS PROVIDED WITH SILENCING BUMPS IN THE OPEN & CLOSED POSITIONS.
 - 7. LEFT HAND SHOWN, RIGHT HAND OPPOSITE.
 - 6. USE ONLY No. 8 SLOTTED PAN OR SLOTTED BINDING HEAD SCREWS FOR MOUNTING THROUGH SLIDE MEMBERS. MAX. .100 HIGH X .380 DIMENSION SCREW HEAD CLEARANCE NECESSARY IN ORDER TO CLEAR DRAWER/BUMPS FROM REVISIONS.
 - 5. WIDTH OF SLIDE MEASURED IN CLOSED POSITION, ACROSS THE BALL BEARINGS. SLIDE MEMBERS AND FOLDI ENGRAVED WITH BALL BEARINGS.
 - 4. FINISH: ELECTRO-PLATING PLATE, (CHROME COATED, (C = CLEAN FIN., CB = BLACK FIN.))
 - 3. LUBRICANT: HIGH-LOW TEMPERATURE GREASE.
 - 2. BALL BEARING: CARBURIZED STEEL.
 - 1. MATERIAL, SLIDE MEMBERS AND COMPONENT PARTS :
- NOTES : UNLESS OTHERWISE SPECIFIED

ACCURIDE
 M.T.S. X
 DATE 08/24/88
 DRAWN 301-2590-12/28
 C