



Accessories

			code
١	HAWA-Assembly wedge for sliding doors running in the ceiling, set for 1 sliding door (See installation drawing page 78)		15770
	Guide profile, plastic black, 3000 mm (9'10 ½"), set of 5 pieces		14963
	Bottom door stop with centering assembly	dull chromium finish	20773
		stainless steel effect	21473
Further accessories see pages 72–86.			

Suspension profiles

auponoion promot			
		mm/inch	code
	Suspension profile, alu plain anodized, predrilled	6500 (21'3 ²⁹ ")	10346
		cut to size	10347
	1.1.6.1		

To spread out the door weight for heavy sliding doors a continuous suspension profile can be used.

Hardware system for wooden sliding doors weighing up to 250 kg (550 lbs.). For low headroom applications.

Description

The HAWA-Junior 250/B is a hardware system with top fixed suspension for low headroom applications and for sliding doors with a weight of up to 250 kg (550 lbs.).

Features of the HAWA-Junior 250/B

- Top fixed suspension
- Low headroom applications
- · Light and silent action
- Adjustable vertically ± 5 mm (⁷/₃₂")
- Track stop, adjustable retaining force

Set for single door, without top track

	code
HAWA-Junior 250/B	21001
For two-panel sliding doors please order two sets for single doors.	_

Set comprising

		pieces	code
	Two-wheeled trolley, M12, with plastic wheels	2	20731
	Top fixed suspension 410 mm (1'4 $\frac{5}{32}$ "), with plate and hanger bolt M12	2	21005
	Cover cap for top fixed suspension, plastic anthracit-grey RAL 7016	2	20907
	Track stop, adjustable retaining force	1	20995
0	Screw-on rubber door stop	1	13114
	Guide, rattle proof, for screw mounting to floor, groove width 14 mm $(\frac{9}{16})$, black plastic	1	14711
	Suspension assembly locking wrench	1	14861

Top tracks

Caution: Hole positions vary.		mm/inch	code
	Top track, alu plain anodized, predrilled	4000 (13'1 ½")	20988
		6000 (19'8 ⁷ / ₃₂ ")	20612
		cut to size	20990
	Connecting bolts for top tracks, set of 2 pieces		21347

Planning/installation

Please use for planning and execution the installation instructions code 17689. (\rightarrow hawa.ch \rightarrow Productfinder)