



Furniture, Cabinet and Display Lighting Systems





Richelieu Hardware Ltd  
7900 Henri-Bourassa Blvd West  
Montreal, Quebec, Canada H4S 1V4

Telephone:  
Canada - 1 800 361-6000  
U.S - 1 800 619-5446

[info@richelieu.com](mailto:info@richelieu.com)  
[www.richelieu.com](http://www.richelieu.com)

Subject to technical changes without  
prior notice. Position as per 11/2008

# Signs and Symbols



Underwriters Laboratories Inc. – Listing mark for the USA



Underwriters Laboratories Inc. – Listing mark for Canada




Intertek Testing Services – Listing mark for the USA



Intertek Testing Services – Listing mark for Canada



New York City Department of Buildings



Necessary hole diameter for recessed spotlight




Maximum bulb wattage which can be used in a particular halogen spotlight



Maximum bulb wattage for MR 11 and MR 16 bulbs which can be used in a particular halogen spotlight



Beam angle



Minimum clearance to combustible materials in front of a spotlight



## What you'll need to buy

### SlimLite XL Fluorescent Light Fixture

Description	Watt	Length	Code No.
ES12	8	12 <sup>7</sup> / <sub>8</sub> "	ES12
ES22	14	23 <sup>1</sup> / <sub>8</sub> "	ES22
ES34	21	34 <sup>7</sup> / <sub>8</sub> "	ES34
ES46	28	46 <sup>3</sup> / <sub>4</sub> "	ES46
ES59	35	58 <sup>7</sup> / <sub>16</sub> "	ES59

Also available with bulb and cover. Add **BC** or **WW BC** (Warm White) to product code.

### Accessories

	Description	Code No.
Power Cord, Connecting Cables, Hardwire Box, Direct Connector and Switch	same as SlimLite, see page 41	
Replacement Bulb	8W Cool White	SFB8
	8W Warm White	SFB8WW
	14W Cool White	SFB14
	14W Warm White	SFB14WW
	21W Cool White	SFB21
	21W Warm White	SFB21WW
	28W Cool White	SFB28
	28W Warm White	SFB28WW
	35W Cool White	SFB35
	35W Warm White	SFB35WW
Plexiglas Cover	for ES12	SPLEX12
	for ES22	SPLEX22
	for ES34	SPLEX34
	for ES46	SPLEX46
	for ES59	SPLEX59

	ES12	ES22	ES34	ES46	ES59
(A) fixture length	12 <sup>7</sup> / <sub>8</sub> "	23 <sup>1</sup> / <sub>8</sub> "	34 <sup>7</sup> / <sub>8</sub> "	46 <sup>3</sup> / <sub>4</sub> "	58 <sup>7</sup> / <sub>16</sub> "
(B) fixture width	29 <sup>1</sup> / <sub>32</sub> "	29 <sup>1</sup> / <sub>32</sub> "	29 <sup>1</sup> / <sub>32</sub> "	29 <sup>1</sup> / <sub>32</sub> "	29 <sup>1</sup> / <sub>32</sub> "
(C) fixture height with diffuser	1 <sup>5</sup> / <sub>16</sub> "	1 <sup>5</sup> / <sub>16</sub> "	1 <sup>5</sup> / <sub>16</sub> "	1 <sup>5</sup> / <sub>16</sub> "	1 <sup>5</sup> / <sub>16</sub> "
(D) tube length	11 <sup>1</sup> / <sub>4</sub> "	21 <sup>1</sup> / <sub>2</sub> "	33 <sup>1</sup> / <sub>4</sub> "	45 <sup>1</sup> / <sub>8</sub> "	57"
(E) tube diameter	T5 (5 <sup>1</sup> / <sub>8</sub> " )	T5 (5 <sup>1</sup> / <sub>8</sub> " )	T5 (5 <sup>1</sup> / <sub>8</sub> " )	T5 (5 <sup>1</sup> / <sub>8</sub> " )	T5 (5 <sup>1</sup> / <sub>8</sub> " )
watts	8	14	21	28	35
lumens	400	1350	2100	2900	3650
current	136 mA	136 mA	198 mA	253 mA	315 mA
in-rush current	less than 5 AMP				
CRI	> 82	> 82	> 82	> 82	> 82
voltage	AC 120	AC 120	AC 120	AC 120	AC 120
frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
maximum watts in line	585 Watts	585 Watts	585 Watts	585 Watts	585 Watts

# SlimLite XL



For longer runs our new SlimLite XL is the solution. The XL offers all the benefits of SlimLite: It's cooler, brighter, more compact. And now it's available in 1', 2', 3', 4' and 5' lengths. This enables continuous rows of light of up to 50 linear feet which makes the XL the perfect lighting system for gondolas, store fixtures and long runs of shelves. SlimLite XL features standard T-5 lamps which are available in a variety of light colors. Its optional plexiglas cover makes it also the preferred light fixture for food applications.

## Product-Features

- Built-in electronic ballast
- Energy efficient, only 14, 21, 28 and 35 W
- Uses standard T-5 lamps, CRI > 82 (to be ordered separately)
- Plug-in modular system permits easy connection for continuous lighting
- Extremely long bulb life, rated 20,000 hrs.
- Available in five different lengths:  
1' ( $12 \frac{7}{8}$ " ), 2' ( $23 \frac{1}{8}$ " ), 3' ( $34 \frac{7}{8}$ " ),  
4' ( $46 \frac{3}{4}$ " ) and 5' ( $58 \frac{7}{16}$ " ) width:  $29 \frac{1}{32}$ " , height:  $1 \frac{7}{16}$ "
- Optional plexiglass cover available (to be ordered separately)
- Contemporary white housing

