

RICHELIEU LIGHTING LAYOUT DESIGN SERVICE

Simply fill out the form below and submit it with your drawing. You will receive a plan back showing where to install each light fixture and a list of components to order. This is a complimentary service, free of charge!



LIGHTING LAYOUT REQUEST FORM

Date Submitted:	
Name:	
Company Name/ Account Number:	
Phone Number:	
Email Address:	
Company Address:	
Project Name:	
Richelieu Sales Rep:	

Please complete the form below to ensure we can provide you with the best layout design based on your project needs.

Elevation and floor plans are **required**, ideally in a CAD .dwg, PDF, or JPEG format. Please only send files related to areas requiring lighting. **Once we receive complete information regarding the layout, the design will be returned within 24-48 hours.**

1. If framed cabinets, how deep is the recessed cavity on the bottom of the cabinet?
2. If frameless cabinets, do these have a light rail? Yes No If yes, then how high?
3. If specifying lighting inside glass cabinets, please indicate on drawings which cabinets those are.
4. Please mark on drawing where outlets, controls and/or switches are located. *If not specified on drawings, Richelieu will specify best outlet location.*
5. Specify the lighting options below:

Specify lighting placement:

- | | |
|---|--|
| <input type="checkbox"/> Under Cabinets | <input type="checkbox"/> Drawer Interior |
| <input type="checkbox"/> Cabinet Interior | <input type="checkbox"/> Toe Kick |
| <input type="checkbox"/> VERTICAL <input type="checkbox"/> HORIZONTAL | <input type="checkbox"/> Countertop Overhang |
| <input type="checkbox"/> Above Cabinets | |

Mounting type:

- Surface _____
- Recessed _____

** If both, please specify placement.*

Kelvin temperature:

- | | |
|--|--|
| <input type="checkbox"/> Warm White (3000 K) | <input type="checkbox"/> Cool White (5000 - 6000 K)
<i>* ONLY FOR GOCCIA AND 12V 4.8 W LED STRIP</i> |
| <input type="checkbox"/> Neutral White (4000 K - 4100 K) | <input type="checkbox"/> Tunable White (TW) (3000 K - 6500 K)
<i>* ONLY FOR ATOM, K-PAD, AND HE6PW TAPE</i> |

6. Specify power supply and compatible switch / sensor to go with it. *(specify if all lights are to be on 1 switch, or if more than 1 are acceptable)*

Power supply:

- Plug-in Installation



Touch Me 30/60W

Call Me 36/72W

Compatible switches:

- Touch Me Dimmer
- Call Me Wireless Dimmer
- DOT Infrared Sensor
- Capsens Invisible Dimmer



Capsens 30/60W

DOT 36/72W

- TW - Touch™ Dimmer
- TW - Single Zone Remote Control
- TW - Three Zone Remote Control



Touch™ TW 60W

TW Remote (SINGLE-ZONE)

TW Remote (THREE-ZONES)

Power supply:

- 2 & 1 Hardwire and Plug-In Installation (Wall Dimmer)



Compatible switches:

- Decora® with Bluetooth® Dimmer Without Dimmer
- IllumaTech Slide Dimmer
- Decora® Rocker Switch (Single-pole, black finish)



Decora® Bluetooth® 450W LED

IllumaTech 150W LED / 120V



Decora® Rocker 15 AMP / 120V

TUNABLE WHITE OPTIONS (TW)

7. Specify lighting product options below, or leave blank and Richelieu will provide the best solution.

12V SYSTEM (Micro12 connectors, black)

SMALLY LED, PUCK LIGHT, 3W

Recessed mount Surface mount 20° angle mount
 Select finish: Aluminum Black/Gray Chrome White

ORBIT LED, PUCK LIGHT, 3W (adjustable spotlight)

Recessed mount Surface mount
 Select finish: Black Chrome

QUADRUM LED, PUCK LIGHT, 3W

Recessed mount
 Select finish: Aluminum Black White

TITAN LED, PANEL LIGHT, 6W

Surface mount, Stainless Steel finish

FLEXYLED CH, TAPE LIGHT (IP20, NOT COATED)

FLEXYLED CR, TAPE LIGHT (IP44, SILICONE COATED)

Surface mount profiles:

Straight, 7/16" H Straight, 1/4" H 45° angle Heat sink

Recessed mount profiles:

Icy, 1/2" D Splitty, (angled) 9/16" D

FLEXYLED SEH4, TAPE LIGHT (IP44, SILICONE COATED)

Side-emitting flexible profile, for recessed installation in 5/32" W x 3/8" D groove

LEAF LED, LINEAR LIGHT

Cabinet Drawer
 Built-in LED and sensor - offered in **fixed widths**

GOCCIA LED, DESIGNER CLOSET ROD

Built-in LED and sensor - offered in **fixed widths**

24V SYSTEM (Micro24 connectors, white)

ATOM LED, PUCK LIGHT, 3W

TUNABLE WHITE OPTION (TW)

Recessed mount Surface mount 20° angle mount
 Select finish: Black Satin Nickel White

K-PAD LED, PANEL LIGHT, 5W

TUNABLE WHITE OPTION (TW)

Surface mount only
 Select type: without sensor With IR sensor With dimmer
 Select finish: Black Stainless Steel White

TRACK, RIGID LED PROFILE

Surface mount only
 Modular LED with semi-transparent diffuser - offered in **fixed lengths**

FLEXYLED LED, TAPE LIGHT (IP22, NOT COATED)

FLEXYLED HE CR, TAPE LIGHT (IP44, SILICONE COATED)

Surface mount profiles:

Straight, 7/16" H Straight, 1/4" H 45° angle Heat sink

Recessed mount profiles:

Icy, 1/2" D Splitty, (angled) 9/16" D

FLEXYLED HE6 PW, TAPE LIGHT (IP20, NOT COATED)

TUNABLE WHITE OPTION (TW)

With the APEX recessed profile

For detailed information and more product selection, view our Lighting Solutions brochure.

Visit www.richelieu.com



SMALLY



ORBIT



QUADRUM



TITAN



ATOM



K-PAD



TRACK



FLEXYLED CH



FLEXYLED CR



FLEXYLED SE H4



FLEXYLED HE6 PW AND APEX



LEAF



GOCCIA

8. Please list any other Richelieu part numbers here: