

- 1** SCREWS AND FASTENERS
- 2** FURNITURE EQUIPMENT
- 3** HINGES
- 4** SLIDES
- 5** CASTERS AND LEGS
- 6** KITCHEN SOLUTIONS
- 7** CLOSET SOLUTIONS
- 8** LIGHTING SOLUTIONS
- 9** SINKS AND FAUCETS
- 10** OFFICE
- 11** SLIDING DOORS
- 12** GLASS HARDWARE
- 13** PANELS AND SURFACES
- 14** EDGE-BANDING
- 15** CABINET DOORS AND DRAWERS
- 16** CORBELS AND FLOOR REGISTERS
- 17** GLUES, SILICONES, CAULK AND INSULATING
- 18** TOOLS AND SECURITY
- 19** FINISHING PRODUCTS AND SHOP SUPPLIES
- 20** COMMERCIAL DISPLAY HARDWARE
- 21** MOLDING, RAILING AND BATHROOM HARDWARE

## FOAM AND FABRIC AEROSOL SPRAY ADHESIVE - SERIES 24

Aerosol adhesive ideal for cushioning applications. The glue is sprayed as a cobweb and remains on the surface of the material.

- Strong adhesion - Sufficient hold that the foam will tear when attempted to remove
- Spray force is adjustable
- High precision spray with filaments
- Offers a flexible assembly line
- Fast-tack adhesive
- Industrial grade

Sold by unit

**Application:** For bonding foam, fabrics, cardboard, or leather to: foam, metal, wood and other substrates

| PRODUCT | FINISH              | WEIGHT        | QTY/BOX |
|---------|---------------------|---------------|---------|
| 20242   | Transparent / Clear | 20 g (0.7 oz) | 12      |



## JOWATHERM 281 GRANULAR EDGE-BANDING HOT MELT

Low-viscosity hot melt with good, elastic adhesion, good resistance to oxydation, as well as good color stability in the melt.

**Application:** For bonding edgebands and for precoating of veneer, melamine resin, PVC, PP and ABS, for square edges and soft forming procedures

| PRODUCT   | FINISH              | WEIGHT        | QTY/BOX |
|-----------|---------------------|---------------|---------|
| JW2814044 | Natural             | 44 lb (20 kg) | 1       |
| JW2814844 | Transparent / Clear |               |         |

**Characteristics:**

- Volume:** Granular
- Material:** EVA copolymer
- Working temperature:** 180-200° C



## JOWAPUR 150.9 PUR LAMINATING ADHESIVE

The Jowapur 150.9 is a unique polyurethane PUR adhesive designed for 3D membrane pressing and vacuum forming applications. This adhesive can be processed without adding a crosslinking agent.

**Application:** For bonding vinyl, particle board and MDF

| PRODUCT  | FINISH | WEIGHT        | QTY/BOX |
|----------|--------|---------------|---------|
| JW150915 | White  | 44 lb (20 kg) | 1       |

**Characteristics:**

- Volume:** Liquid
- Material:** Polyurethane
- Working temperature:** Min. 15° C



## JOWAT 148.60 PRIMER

Low to medium viscosity copolymer emulsion with excellent adhesion to coated surfaces. Specifically used to prime HPL before edgebanding with EVA glues on your edgebander.

**Application:** For laminating HPL, vinyl films (reverse printed and regular), and lightweight paper foils (non-impregnated) to wood substrates

Sold by unit

| PRODUCT    | FINISH              | WEIGHT      | QTY/BOX |
|------------|---------------------|-------------|---------|
| JW14860111 | Transparent / Clear | 9 lb (4 kg) | 4       |

**Characteristics:**

- Volume:** Liquid
- Material:** Copolymer emulsion
- Working temperature:** Min. 15° C



### CONSTRUCTION ADHESIVE - GENERAL PURPOSE

This adhesive delivers the perfect combination of convenience and performance for interior projects.

**Application:** For premium grade adhesive ideal for general construction, remodeling, maintenance, and repair projects

Sold by unit

| PRODUCT  | FINISH | WEIGHT          | QTY/BOX |
|----------|--------|-----------------|---------|
| D0158244 | White  | 10.3 oz (292 g) | 12      |

**Characteristics:**

**Base:** Acrylic latex resin



### LIQUIDLOX ADHESIVE

Liquidlox is a general purpose, middle viscosity, high strength fast cure adhesive.

- Ethyl cyanoacrylate adhesive
- Color: colorless transparent
- Service temperature range: -50 to 80° C
- 15 second quick cure

Sold by unit

| PRODUCT | FINISH              | WEIGHT        | QTY/BOX |
|---------|---------------------|---------------|---------|
| 4222002 | Transparent / Clear | 20 g (0.7 oz) | 48      |

**Suggested product(s):**

| PRODUCT  | DESCRIPTION          |
|----------|----------------------|
| 422202SK | Striplox Starter Kit |



### 7709TG LAMINATING ADHESIVE

Hot melt material to clean melting units, hoses, and application units in which reactive PUR hot melt adhesives are processed.

**Application:** For veneer, HPL to particleboards, MDF, plywood, and wood. Excellent adhesion to veneer, decorative laminates, particleboard, plywood, and more.

| PRODUCT  | FINISH | WEIGHT | QTY/BOX |
|----------|--------|--------|---------|
| 7709TG05 | Green  | 5 gal  | 1       |
| 7709TG55 |        | 55 gal |         |

**Characteristics:**

**Volume:** Liquid  
**Material:** Vinyl acetate  
**Working temperature:** 13-29° C



### KLEIBERIT 761.7 PURGING AGENT FOR PUR ADHESIVE

Hot melt material to clean melting units, hoses, and application units in which reactive PUR hot melt adhesives are processed renders nozzles clog free.

**Application:** Used for application devices fitted with nozzles

Sold by bag

| REF. | PRODUCT | FINISH              | VOLUME    | WEIGHT         | QTY/BOX |
|------|---------|---------------------|-----------|----------------|---------|
| A    | 761300  | Transparent / Clear | Cartridge | 8.8 oz (250 g) | 12      |
| B    | 761720  | Blue                | Granular  | 44 lb (20 kg)  | 1       |

**Characteristics:**

**Material:** EVA copolymers  
**Working temperature:** 120-140° C



- 1** SCREWS AND FASTENERS
- 2** FURNITURE EQUIPMENT
- 3** HINGES
- 4** SLIDES
- 5** CASTERS AND LEGS
- 6** KITCHEN SOLUTIONS
- 7** CLOSET SOLUTIONS
- 8** LIGHTING SOLUTIONS
- 9** SINKS AND FAUCETS
- 10** OFFICE
- 11** SLIDING DOORS
- 12** GLASS HARDWARE
- 13** PANELS AND SURFACES
- 14** EDGE-BANDING
- 15** CABINET DOORS AND DRAWERS
- 16** CORBELS AND FLOOR REGISTERS
- 17** GLUES, SILICONES, CAULK AND INSULATING
- 18** TOOLS AND SECURITY
- 19** FINISHING PRODUCTS AND SHOP SUPPLIES
- 20** COMMERCIAL DISPLAY HARDWARE
- 21** MOLDING, RAILING AND BATHROOM HARDWARE

## KLEIBERIT 707.6 PUR HOT MELT ADHESIVE

Unrivaled joint strength that creates chemical crosslinking when in contact with humidity.

- Enables invisible glue line
- Closer tighter joint than EVA glue
- High level of thermal resistance (-30°C to 150°C)
- Very high level of resistance to moisture, water, and vapor

**Application:** For thick PVC or ABS edgbanding, laminates, solid wood

Sold as a box of 18 bags, 400 g per bag

| PRODUCT    | FINISH            | WEIGHT           | QTY/BOX |
|------------|-------------------|------------------|---------|
| 7076084511 | Transparent/Clear | 15.4 lb (7.2 kg) | 18      |
| 7076104530 | White             |                  |         |

### Characteristics:

**Material:** Polyurethane  
**Working temperature:** 120-140° C



## KLEIBERIT 707.9 PUR HOT MELT ADHESIVE

KLEIBERIT PUR HM 707.9 is a tried and tested product for zero-joint application.

These hotmelt adhesive systems react with moisture from the material to be bonded or the working environment, e.g., the air; meaning in addition to the physical effect through the hardening of the liquid adhesive, there is also an additionally chemical reaction which positively influences the bond properties. With regards to the bonding properties or water and temperature resistance.

Sold as a box of 18 bags, 400 g per bag

**Application:** For thick PVC or ABS edgbanding

| PRODUCT    | FINISH  | VOLUME    | WEIGHT           | WORKING TEMPERATURE | QTY/BOX |
|------------|---------|-----------|------------------|---------------------|---------|
| 7079008211 | Natural | Cartridge | 2.2 lb (1.56 kg) | 130-150° C          | 6       |
| 7079108230 | White   |           |                  |                     |         |
| 7079084511 | Natural | Granular  | 15.4 lb (7.2 kg) | 120-150° C          | 18      |

### Characteristics:

**Material:** Polyurethane



## LIONGRIP PROMOTIONAL KIT

- High heat resistance and performance
- Fast grab
- Easy and uniform coverage
- High tack and excellent contactability
- Spray force is adjustable via the spray gun

**Application:** Excellent adhesion to a variety of substrates including, but not limited to laminates, particle board, plywood, hardwood, leather, rubber, and metal

### Included:

- 12' (3.65 m) tube, WSB12
- Spray gun, AA23L45885
- Spray tip
- LIONGRIP R015NF 20 lb (9 kg) contact glue canister

| PRODUCT    | FINISH | WEIGHT       | QTY/BOX |
|------------|--------|--------------|---------|
| R015NFP20C | Clear  | 20 lb (9 kg) | 1       |



